

OXYGEN- oxygen gas Lessors, Incorporated

oxygen

OXYGEN, COMPRESSED USP UN1072

OXYGEN 2


WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.

CAUTION: Federal law prohibits dispensing without prescription. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil, grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. Use back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52C (125F). Use in accordance with the Material Safety Data Sheets (MSDS). CAS: 7782-44-7 **DO NOT REMOVE THIS PRODUCT LABEL.**

LESSORS, INC. 1300 N. GENESEE RD. BURTON, MI 48509 810-742-2302
40035 (R 01/05)



OXYGEN, REFRIGERATED USP UN1073

OXYGEN 2

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

CONTENTS:

LOT #:

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

WARNING: EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin, or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Cylinder temperature should not exceed 52C (125F). Close valve after each use and when empty. Use in accordance with the Material Safety Data Sheets (MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

LESSORS, INC. 1300 N. GENESEE RD. BURTON, MI 48509 810-742-2302
47136 10/00

OXYGEN, COMPRESSED USP

UN1072



WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **R_x only**.
Caution: Federal law prohibits dispensing without prescription. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. **Produced by Air Liquefaction.**

WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52°C (125°F). Use in accordance with the **Material Safety Data Sheet (MSDS)**.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

LESSORS, INC.

1300 N. GENESEE RD • BURTON, MI 48509
810-742-2302

40035
(R 01/05)

OXYGEN, COMPRESSED USP UN1072

OXYGEN 2 18033 (R 04/05)

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation.

For all other medical applications, Rx only.

CAUTION: Federal law prohibits dispensing without prescription. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52C (125F). Use in accordance with the Material Safety Data Sheets (MSDS). CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

LESSORS, INC. 1300 N. GENESEE RD. BURTON, MI 48509 810-742-2302

OXYGEN, REFRIGERATED LIQUID

USP



UN1073

↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑

CONTENTS: _____

LOT #: _____

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only.**

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing

arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING: EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE.
VIGOROUSLY ACCELERATES COMBUSTION.
COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT
CAN CAUSE SEVERE FROSTBITE.
Keep oil, grease, and combustibles away.
Use only with equipment cleaned for oxygen service.
Store and use with adequate ventilation.
Do not get liquid in eyes, on skin, or clothing.
For liquid withdrawal, wear face shield and gloves.
Do not drop. Use suitable hand truck for container movement.
Avoid spills. Do not walk on or roll equipment over spills.
Cylinder temperature should not exceed 52°C (125°F)
Close valve after each use and when empty.
Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

LESSORS, INC.

1300 N. GENESEE RD • BURTON, MI 48509
810-742-2302

47136
10/00

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:55404-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	995 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:55404-001-01	40 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1964	
2	NDC:55404-001-02	113 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1964	
3	NDC:55404-001-03	164 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1964	
4	NDC:55404-001-04	170 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1964	
5	NDC:55404-001-05	198 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1964	
6	NDC:55404-001-06	410 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1964	
7	NDC:55404-001-07	647 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1964	
8	NDC:55404-001-08	680 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1964	
9	NDC:55404-001-09	1699 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1964	
10	NDC:55404-001-10	3454 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1964	
11	NDC:55404-001-11	3540 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1964	
12	NDC:55404-001-12	3993 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1964	
13	NDC:55404-001-13	7108 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1964	
14	NDC:55404-001-14	7986 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1964	
15	NDC:55404-001-15	8665 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1964	
16	NDC:55404-001-16	9543 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1964	
17	NDC:55404-001-17	16750 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1964	
18	NDC:55404-001-18	28257 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1964	
19	NDC:55404-001-19	33500 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1964	
20	NDC:55404-001-20	146311 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1964	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205767	01/01/1964	

Labeler - Lessors, Incorporated (041806169)

Establishment

Name	Address	ID/FEI	Business Operations
Lessors, Incorporated		041806159	manufacture(55404-001)

