

AIR- air gas
AGL Welding Supply CO., Inc.

air

AIR, COMPRESSED

UN1002

MEDICAL AIR, USP

Rx only.

WARNING: Administration of Medical Air may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Medical Air and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

SUPPORTS COMBUSTION.

Do not handle until all safety precautions have been read and understood.

Use a back flow preventive device in the piping.

Close valve after each use and when empty.

Use only with equipment rated for cylinder pressure.

Do not open valve until connected to equipment prepared for use.

Protect from sunlight when ambient temperature exceeds 52 C (125 F).

Read and follow the Safety Data Sheet (SDS) before use.

Manufactured by:

AGL

CERTIFIED ISO 9001

AGL Inhalation Therapy Co.

600 Route 46 West

Clifton, NJ 07015

NJ Tel: 973-478-5000

NY Tel: 845-561-5900

CAS: 132259-10-0

DO NOT REMOVE THIS PRODUCT LABEL

**AIR,
COMPRESSED**

UN1002

MEDICAL AIR, USP



Manufactured by:



AGL

CERTIFIED ISO 9001

AGL Inhalation Therapy Co.
600 Route 46 West
Clifton, NJ 07015
NJ Tel: 973-478-5000
NY Tel: 845-561-5900

CAS: 132259-10-0



**DO NOT REMOVE
THIS PRODUCT LABEL**

AGL-8-D-271-4 (4/25)

Rx only.

WARNING: Administration of Medical Air may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Medical Air and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. SUPPORTS COMBUSTION.

- Do not handle until all safety precautions have been read and understood.
- Use a back flow preventive device in the piping.
- Close valve after each use and when empty.
- Use only with equipment rated for cylinder pressure.
- Do not open valve until connected to equipment prepared for use.
- Protect from sunlight when ambient temperature exceeds 52°0 (125°F).
- Read and follow the Safety Data Sheet (SDS) before use.

AIR			
air gas			
Product Information			
Product Type	PRESCRIPTION ANIMAL DRUG	Item Code (Source)	NDC:17575-017
Route of Administration	RESPIRATORY (INHALATION)		
Active Ingredient/Active Moiety			
Ingredient Name	Basis of Strength	Strength	
Air (UNII: K21NZZ5Y0B) (Air - UNII:K21NZZ5Y0B)	Air	1000 mL in 1 L	
Packaging			
#	Item Code	Package Description	Marketing Start Date
1	NDC:17575-017-01	8637 L in 1 CYLINDER	
2	NDC:17575-017-02	6570 L in 1 CYLINDER	
3	NDC:17575-017-03	4165 L in 1 CYLINDER	
4	NDC:17575-017-04	3388 L in 1 CYLINDER	
5	NDC:17575-017-05	610 L in 1 CYLINDER	
Marketing Information			
Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date

NADA	NADA141365	01/01/1966	
------	------------	------------	--

Labeler - AGL Welding Supply CO., Inc. (011186004)

Establishment

Name	Address	ID/FEI	Business Operations
AGL Welding Supply CO., Inc.		011186004	manufacture

Revised: 10/2025

AGL Welding Supply CO., Inc.