OXYGEN - oxygen gas Two MP Investments, Inc. dba Respicare

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.

Oxygen

PACKAGE LABEL PRINCIPAL DISPLAY PANEL

Produced by air liquefaction

OXYGEN COMPRESSED U.S.P. UN 1072

OXYGEN 2

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications: **Rx ONLY.** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

WARNING: HIGH PRESSURE OXIDIZING GAS VIGOROUSLY ACCELERATES COMBUSTION

- Use only with pressure equipment and apparatus cleaned and designed for oxygen service and rated for cylinder pressure.
- Open valve slowly. Close valve after each use and when empty. Keep cylinder, cylinder valve, all equipment that connects, free of oil and grease to avoid violent ignition.
- Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Food, Drug and Cosmetic Act.
- Pursuant to recommendation by Compressed Gas Association (CGA C-7-2000), do not expose pressurized cylinders to temperatures in excess of 125° F.
- DO NOT REMOVE THIS PRODUCT LABEL.

use only in accordance with product instructions and material safety data sheet.

Distributed by:


Respicare Home Respiratory Care 7411 Alban Station Court, Suite A100 Springfield, Virginia 22150 (703) 440-3600 (800) 881-9207

WARNING:

HIGH PRESSURE GAS CYLINDER

Improper filling or abuse of this cylinder, or failure to heed this warning may cause serious injury or loss of life. DO NOT ALTER OR MODIFY CYLINDER OR RELATED COMPONENTS. DO NOT OVER PRESSURIZE. Keep out of reach of children. Cylinders that have been refinished and/or exposed to elevated temperatures must be hydrostatically tested before filling. do not use

caustic paint strippers. Aluminum cylinders subject to action of fire or heated to temperatures in excess of 350° F must be withdrawn from service and condemned. Valves and safety relief devices must be removed and replaced by trained personnel. Do not alter or change safety discs. Replace pressure relief devices only with complete assemblies supplied by the valve manufacturer. DO NOT FILL WITH OXIDIZING GASES WITHOUT PROPER CLEANING. Cylinders, valves, and assemblies must be specially cleaned for oxygen. Verify cylinder content and monthly, or more frequently if required. Store and use with adequate ventilation.



WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications: Rx ONLY. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

WARNING: HIGH PRESSURE OXIDIZING GAS VIGOROUSLY ACCELERATES COMBUSTION

- Use only with pressure reducing equipment and apparatus cleane service and rated for cylinder pressure.
- > Open valve slowly. Close valve after each use and when empty. Keep cylinder, cylinder valve, all
- Open valve slowly. Close valve after each use and when empty. Keep cylinder, cylinder valve, all equipment that connects, free of oil and grease to avoid violent ignition.
 Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.
 Pursuant to recommendations by Compressed Gas Association (CGA C-7-2000), do not expose pressurized cylinders to temperatures in excess of 125°F.
 DO NOT REMOVE THIS PRODUCT LABEL.
 Use only in accordance with product instructions and material safety data sheet.

Date code: 1201

Distributed by:



7411 Alban Station Court, Suite A100 Springfield, Virginia 22150

> (703) 440-3600 (800) 881-9207

WARNING: HIGH PRESSURE GAS CYLINDER

Improper filling or abuse of this cylinder, or failure to heed this warning may cause serious injury or loss of life. DO NOT ALTER OR MODIFY CYLINDER OR RELATED COMPONENTS. DO NOT OVER PRESSURIZE. Keep out of the reach of children. Cylinders that have been refinished and/or exposed to elevated between the components. and/or exposed to elevated temperatures must be hydrostatically tested before filling. Do not use caustic paint strippers. Aluminum cylinde subject to action of fire or heated to temperatures in excess of 350°F must be withdrawn from service and condemned. Valves and safety relief devices must be removed and replaced by trained personnel. Do not alter or change safety discs. Replace pressure relief devices only with complete assemblies supplied by the valve manufacturer. DO NOT FILL WITH OXIDIZING GASES WITHOUT PROPER CLEANING. Cylinders, valves, and assemblies must be specially cleaned for oxygen. Verify cylinder content and pressure monthly, or more frequently if required. Store and use with adequate ventilation.

OXYGEN

oxygen gas

Product Information	Product Information			
Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:67152-001	
Route of Administration	RESPIRATORY (INHALATION)			

P	Active Ingredient/Active Moiety			
	Ingredient Name	Basis of Strength	Strength	
C	DXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	1 L in 1 L	

Packaging				
#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:67152-001-01	685 L in 1 CYLINDER		
2	NDC:67152-001-02	416 L in 1 CYLINDER		
3	NDC:67152-001-03	249 L in 1 CYLINDER		
4	NDC:67152-001-04	165 L in 1 CYLINDER		
5	NDC:67152-001-05	114 L in 1 CYLINDER		

Marketing Information				
Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date	
unapproved medical gas		10/28/2010		

Labeler - Two MP Investments, Inc. dba Respicare (132283925)

Establishment				
Name	Address	ID/FEI	Business Operations	
Two MP Investments, Inc. dba Respicare		132283925	manufacture	

Revised: 10/2010 Two MP Investments, Inc. dba Respicare