OXYGEN- oxygen gas Shasta Welding Supply, Inc.

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.

Oxygen, USP

Principal for Oxygen Product



OXYGEN

COMPRESSED

USP

UN 1072

PRODUCED BY AIR LIQUIFICATION

WARNING: HIGH PRESSURE OXIDIZING GAS, VIGOROUSLY ACCELERATES

COMBUSTION. NO SMOKING IN THE PRESENCE OF OXYGEN OR A FIRE MAY RESULT.


WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.

WARNING: Federal law prohibits dispensing without prescription. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjuction with resuscitative equipment.

WARNING: Keep oil and grease away. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. Open valve slowly. Close valve after each use and when empty.

USE IN ACCORDANCE WITH MATERIAL SAFETY DATA SHEET.

DO NOT REMOVE THIS PRODUCT LABEL.



INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from dothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment deaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID:

IF ON SKIN: <u>Thaw frosted parts with lukewarm water. Do not rub affected</u> <u>area. Get immediate medical advice/attention</u>.

DO NOT REMOVE THIS PRODUCT LABEL.

Warning: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

Representative Labeling pursuant to 21 CFR 207.3 (10) Company name and contact information are printed in this area

OXYGEN,	
REFRIGERATED	
LIQUID USP	
UN 1073	
CONTENTS	LITERS
CAS NO: 7782-44-7	
DANGER:	
MAY CAUSE OR INTENSIFY F	IRE; OXIDIZER. CONTAINS
REFRIGERATED GAS; MAY C	AUSE CRYOGENIC BURNS OR
INJURY. COMBUSTIBLES IN (CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON

IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use. FIRST AID:

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL.

Warning: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.



Representative Labeling pursuant to 21 CFR 207.3 (10)

0)	KYGEN					
оху	/gen gas					
Pı	roduct Infor	mation				
Product Type			HUMAN PRESCRIPTION DRUG	Item Code (Source)		IDC:58878-001
Route of Administration		istration	RESPIRATORY (INHALATION)			
Δα	tive Ingredi	ent/Active	Moiety			
Active Ingredient/Active Moiety Ingredient Name Basis of Strength Stren				Strength		
ох	YGEN (UNII: S88	-	GEN - UNII:S88TT14065)	OXYGEN	•	99 L in 100 L
Pa	ckaging					
Pa #	ckaging Item Code	Pa	ckage Description	Marketing Start	Ma	nrketing End
			Ckage Description (LINDER; Type 0: Not a Combination	Marketing Start Date	Ma	nrketing End Date
#	Item Code	3455 L in 1 CY Product		Date	Ma	-
# 1	Item Code NDC:58878- 001-03 NDC:58878-	3455 L in 1 CY Product 425 L in 1 CYL Product	'LINDER; Type 0: Not a Combination	Date 11/12/2019	Ma	-
# 1 2	Item Code NDC:58878- 001-03 NDC:58878- 001-04 NDC:58878-	3455 L in 1 CY Product 425 L in 1 CYL Product 640 L in 1 CYL Product	'LINDER; Type 0: Not a Combination	Date 11/12/2019 11/12/2019	Ma	-
# 1 2 3	Item Code NDC:58878- 001-03 NDC:58878- 001-04 NDC:58878- 001-05 NDC:58878- 001-05	3455 L in 1 CY Product 425 L in 1 CYL Product 640 L in 1 CYL Product 113 L in 1 CYL Product	'LINDER; Type 0: Not a Combination INDER; Type 0: Not a Combination INDER; Type 0: Not a Combination	Date 11/12/2019 11/12/2019 11/12/2019 11/12/2019	Ma	-
# 1 2 3 4	Item Code NDC:58878- 001-03 NDC:58878- 001-04 NDC:58878- 001-05 NDC:58878- 001-06 NDC:58878- 001-06	3455 L in 1 CYL Product 425 L in 1 CYL Product 640 L in 1 CYL Product 113 L in 1 CYL Product 164 L in 1 CYL Product	'LINDER; Type 0: Not a Combination INDER; Type 0: Not a Combination INDER; Type 0: Not a Combination INDER; Type 0: Not a Combination	Date 11/12/2019 11/12/2019 11/12/2019 11/12/2019 11/12/2019	Ma	-
# 1 2 3 4 5	Item Code NDC:58878- 001-03 NDC:58878- 001-04 NDC:58878- 001-05 NDC:58878- 001-06 NDC:58878- 001-07 NDC:58878- 001-07	3455 L in 1 CYL Product 425 L in 1 CYL Product 640 L in 1 CYL Product 113 L in 1 CYL Product 164 L in 1 CYL Product 255 L in 1 CYL Product	'LINDER; Type 0: Not a Combination INDER; Type 0: Not a Combination	Date 11/12/2019 11/12/2019 11/12/2019 11/12/2019 11/12/2019 11/12/2019	Ma	-

gus	·					
una gas	approved medical		11/12/2019			
	Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date		
Μ	Marketing Information					
12	NDC:58878- 001-10	4248 L in 1 CYLINDER; Type 0: Not a Combination Product	11/12/2019			
11	NDC:58878- 001-12	1133 L in 1 CYLINDER; Type 0: Not a Combination Product	11/12/2019			
10	NDC:58878- 001-11	2266 L in 1 CYLINDER; Type 0: Not a Combination Product	11/12/2019			
9	NDC:58878- 001-02	7080 L in 1 CYLINDER; Type 0: Not a Combination Product	11/12/2019			

Labeler - Shasta Welding S	Supply, Inc.	(112683677)
----------------------------	--------------	-------------

Establishment					
Name	Address	ID/FEI	Business Operations		
Shasta Welding Supply, Inc.		112683677	manufacture(58878-001)		

Revised: 11/2024

Shasta Welding Supply, Inc.