

OXYGEN- oxygen gas
PURITY CYLINDER GASES INC

Oxygen

OXYGEN, COMPRESSED USP

UN1072

PRODUCED BY AIR LIQUEFACTION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

PURITY CYLINDER GASES INC.

2580 28th St. SW

Wyoming, MI 49519

(616) 532-2375

NO SMOKING

NO VAPING

CONTENTS:

LTRS: CU.FT

At 70 F and 2400 psi

OXYGEN,
COMPRESSED
USP
UN1072
PRODUCED BY AIR LIQUEFACTION



WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use.



2580 28th St. SW
Wyoming, MI 49519
(616) 532-2375

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

CONTENTS:
LBS: CU. FT.
at 70 F and 2400 psi.



NO SMOKING
NO VAPING

OXYGEN, COMPRESSED USP

UN1072

PRODUCED BY AIR LIQUEFACTION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

PURITY CYLINDER GASES INC.

2580 28th St. SW

Wyoming, MI 49519

(616) 532-2375


NO SMOKING

NO VAPING

CONTENTS:

LTRS: CU.FT

At 70 F and 2400 psi



OXYGEN

REFRIGERATED LIQUID, USP

UN 1073

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

WARNING

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

DANGER

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT.

Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use only outdoors or with adequate ventilation. Store in a well-ventilated place. Wear cold insulating gloves and either face shield or eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet

(SDS) before use.

READ AND FOLLOW THE SAFETY DATA SHEET (SDS) BEFORE USE.

CAS: 7782-44-7

NO SMOKING

NO VAPING

FIRST AID

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical help.

Contents:

PURITY CYLINDER GASES INC.

2580 28th St. SW

Wyoming, MI 49519

(616) 532-2375

OXYGEN
REFRIGERATED LIQUID, USP
UN 1073



ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

<p>WARNING</p> <p>For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, RX required.</p> <p>Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.</p> <p>Produced by Air Liquefaction.</p> <p>READ AND FOLLOW THE SAFETY DATA SHEET (SDS) BEFORE USE. CAS: 7782-44-7</p>	<p>DANGER</p> <p>MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT.</p> <p>Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use only outdoors or with adequate ventilation. Store in a well-ventilated place. Wear cold insulating gloves and either face shield or eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.</p>	 <p>IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical help.</p> <p>Contents:</p>	
--	---	---	---

PURITY CYLINDER GASES, INC
2580 28th Street SW
Wyoming MI 49509
(616) 532-2375

DO NOT REMOVE THIS PRODUCT LABEL

PRINTED BY RATERMANN MFG., INC. www.rmlorder.com

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:10927-003
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:10927-003-09	113 L in 1 CYLINDER; Type 0: Not a Combination Product	10/20/1938	
2	NDC:10927-003-10	142 L in 1 CYLINDER; Type 0: Not a Combination Product	10/20/1938	
3	NDC:10927-003-11	255 L in 1 CYLINDER; Type 0: Not a Combination Product	10/20/1938	
4	NDC:10927-003-12	396 L in 1 CYLINDER; Type 0: Not a Combination Product	10/20/1938	
5	NDC:10927-003-13	651 L in 1 CYLINDER; Type 0: Not a Combination Product	10/20/1938	
6	NDC:10927-003-14	1388 L in 1 CYLINDER; Type 0: Not a Combination Product	10/20/1938	12/31/2023
7	NDC:10927-003-15	1699 L in 1 CYLINDER; Type 0: Not a Combination Product	10/20/1938	12/31/2023
8	NDC:10927-003-16	3597 L in 1 CYLINDER; Type 0: Not a Combination Product	10/20/1938	
9	NDC:10927-003-17	7420 L in 1 CYLINDER; Type 0: Not a Combination Product	10/20/1938	
10	NDC:10927-003-18	9657 L in 1 CYLINDER; Type 0: Not a Combination Product	10/20/1938	
11	NDC:10927-003-19	1132.68 L in 1 CYLINDER; Type 0: Not a Combination Product	10/20/1938	
12	NDC:10927-003-20	589 L in 1 CYLINDER; Type 0: Not a Combination Product	10/20/1938	
13	NDC:10927-003-21	1252 L in 1 CYLINDER; Type 0: Not a Combination Product	10/20/1938	
14	NDC:10927-003-22	10 L in 1 DEWAR; Type 0: Not a Combination Product	10/20/1938	
15	NDC:10927-003-23	20 L in 1 DEWAR; Type 0: Not a Combination Product	10/20/1938	
16	NDC:10927-003-24	30 L in 1 DEWAR; Type 0: Not a Combination Product	10/20/1938	
17	NDC:10927-003-25	40 L in 1 DEWAR; Type 0: Not a Combination Product	10/20/1938	
18	NDC:10927-003-26	160 L in 1 DEWAR; Type 0: Not a Combination Product	10/20/1938	
19	NDC:10927-003-27	200 L in 1 DEWAR; Type 0: Not a Combination Product	10/20/1938	
20	NDC:10927-003-28	450 L in 1 DEWAR; Type 0: Not a Combination Product	10/20/1938	
21	NDC:10927-003-29	719 L in 1 DEWAR; Type 0: Not a Combination Product	10/20/1938	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205767	10/20/1938	

Labeler - PURITY CYLINDER GASES INC (065878860)

Establishment

Name	Address	ID/FEI	Business Operations
PURITY CYLINDER GASES INC		006055710	manufacture(10927-003)

Establishment

Name	Address	ID/FEI	Business Operations
PURITY CYLINDER GASES INC		120042374	manufacture(10927-003)

Revised: 12/2025

PURITY CYLINDER GASES INC