

OXYGEN- oxygen gas
Arcet Equipment Company dba Arc3 Gases North

Oxygen

OXYGEN, COMPRESSED USP
UN1072

PRODUCED BY AIR LIQUEFACTION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

ARC3 GASES
1636 Hwy 301 South Dunn, NC 28334
1700 Chamberlayne Ave. Richmond, VA 23222
844-534-8021
NO SMOKING
NO VAPING



OXYGEN, COMPRESSED USP
UN1072

PRODUCED BY AIR LIQUEFACTION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

ARC3 GASES

1636 Hwy 301 South Dunn, NC 28334

1700 Chamberlayne Ave. Richmond, VA 23222

844-534-8021

NO SMOKING

NO VAPING



OXYGEN, Refrigerated Liquid USP

UN 1073

ARC3 GASES

1636 Hwy 301 South Dunn, NC 28334

1700 Chamberlayne Ave. Richmond, VA 23222

844-534-8021

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

WARNING:

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use only outdoors or with adequate ventilation. Store in a well-ventilated place. Wear cold insulating gloves and either face shield or eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid Spills. Do not walk on or roll equipment over spills. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL.

CAS: 7782-44-7

NO SMOKING NO VAPING



OXYGEN			
oxygen gas			
Product Information			
Product Type	PRESCRIPTION ANIMAL DRUG	Item Code (Source)	NDC:59788-011

Route of Administration RESPIRATORY (INHALATION)

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	995 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:59788-011-10	103 L in 1 CYLINDER		
2	NDC:59788-011-11	126.4 L in 1 CYLINDER		
3	NDC:59788-011-12	149.6 L in 1 CYLINDER		
4	NDC:59788-011-13	198 L in 1 CYLINDER		
5	NDC:59788-011-14	225.9 L in 1 CYLINDER		
6	NDC:59788-011-15	420 L in 1 CYLINDER		
7	NDC:59788-011-16	588.4 L in 1 CYLINDER		
8	NDC:59788-011-17	690 L in 1 CYLINDER		
9	NDC:59788-011-18	1132.8 L in 1 CYLINDER		
10	NDC:59788-011-19	1567.3 L in 1 CYLINDER		
11	NDC:59788-011-20	2548.8 L in 1 CYLINDER		
12	NDC:59788-011-21	3160 L in 1 CYLINDER		
13	NDC:59788-011-22	3172 L in 1 CYLINDER		
14	NDC:59788-011-23	6270 L in 1 CYLINDER		
15	NDC:59788-011-24	8510 L in 1 CYLINDER		
16	NDC:59788-011-25	127100 L in 1 DEWAR		
17	NDC:59788-011-26	141500 L in 1 DEWAR		
18	NDC:59788-011-27	179803 L in 1 DEWAR		
19	NDC:59788-011-28	206472 L in 1 DEWAR		
20	NDC:59788-011-29	16750 L in 1 DEWAR		
21	NDC:59788-011-30	24950 L in 1 DEWAR		
22	NDC:59788-011-31	25650 L in 1 DEWAR		
23	NDC:59788-011-32	29069 L in 1 DEWAR		
24	NDC:59788-011-33	33500 L in 1 DEWAR		
25	NDC:59788-011-34	33620 L in 1 DEWAR		
26	NDC:59788-011-35	37619 L in 1 CYLINDER		
27	NDC:59788-011-36	7760 L in 1 CYLINDER		

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NADA	NADA141354	05/01/1986	

Labeler - Arcet Equipment Company dba Arc3 Gases North (002812691)

Establishment

Name	Address	ID/FEI	Business Operations
Arcet Equipment Company dba Arc3 Gases North		827002668	manufacture

Establishment

Name	Address	ID/FEI	Business Operations
Arcet Equipment Company dba Arc3 Gases North		005693077	manufacture

Establishment

Name	Address	ID/FEI	Business Operations
Arcet Equipment Company dba Arc3 Gases North		169286411	manufacture

Establishment

Name	Address	ID/FEI	Business Operations
Arc3 Gases Inc.		117463198	manufacture

Revised: 12/2025

Arcet Equipment Company dba Arc3 Gases North