HELIUM/OXYGEN MIX- helium/oxygen mix gas NexAir, LLC

Helium/Oxygen Mix Label

COMPRESSED GAS, N.O.S. (OXYGEN HELIUM) UN1956 20% OXYGEN USP 80% HELIUM USP MIXTURE

CAS: (7782-44-7) (7440-59-7) Rx only

WARNING: Administration of this gas mixture may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of gas mixtures and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications, and side effects and the precautions to be taken. WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

Do not handle until all safety precautions have been read and understood. Avoid breathing gas. Use and store only outdoors or in a well-ventilated place. Use a back flow preventive device in the piping. Use only with equipment rated for cylinder pressure. Close valve after each use and when empty. when Protect from sunlight when ambient temperature exceeds 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet.

FIRST AID: IF ACCIDENTALLY INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

NET CONTENTS Cylinder Size Cubic Feet Liters (Gaseous) K 200.4 5675 E 22.0 625 D-puritan 13.5 382

DO NOT REMOVE THIS PRODUCT LABEL

Distributed by nexAir nexAir, LLC . www.nexAir.com

1385 Corporate Ave. . Memphis, TN 38132 . 888-639-2474

COMPRESSED GAS, N.O.S.

(OXYGEN, HELIUM)

UN1956



20% OXYGEN USP 80% HELIUM USP MIXTURE

CAS: (7782-44-7) (7440-59-7)

R_c Only

WARNING: Administration of this gas mixture may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of gas mixtures, and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

Do not handle until all safety precautions have been read and understood. Avoid breathing gas. Use and store only outdoors or in a well-ventilated place. Use a back flow preventive device in the piping. Use only with equipment rated for cylinder pressure. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet

FIRST AID: IF ACCIDENTALLY INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

Cylinder Size	NET CONTENTS Cubic Feet	Liters (Gaseous)	
К	200.4	5675	
E	22.0	625	
D-puritan	13.5	382	

DO NOT REMOVE THIS PRODUCT LABEL.



nexAir, LLC • www.nexAir.com 1385 Corporate Ave. • Memphis, TN 38132 888-639-2474

NON-FLAMMABLE GAS 2 OXIDIZER 5.1 Rx only


USP % OXYGEN, USP % HELIUM USP MIXTURE CAS: (7782-44-7) (7440-59-7)

WARNING: Administration of this gas mixture may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of gas mixtures and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications, and side effects and the precautions to be taken. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when Protect from sunlight when ambient temperature exceeds 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet (SDS) before use.

NET CONTENTS Contains Cubic Feet at 70 degrees F and PSIG DO NOT REMOVE THIS PRODUCT LABEL
Net Contents Cubic Feet: Liters:

nexAir

Distributed by nexAir, LLC . www.nexAir.com 1385 Corporate Ave. . Memphis, TN 38132 . 888-639-2474



warning: Administration of this gas mixture may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of gas mixtures, and is familiar with the indications of facts decorate matheds, and frequency and duration of

with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet (SDS) before use.

DO NOT REMOVE THIS PRODUCT LABEL

t Contents	
Liters:	

nex/lif.

Distributed by nexAir, LLC • www.nexAir.com 1385 Corporate Ave. • Memphis, TN 38132 • 888-639-2474

HELIUM/OXYGEN MIX

helium/oxygen mix gas

Product Information			
Product Type	PRESCRIPTION ANIMAL DRUG	Item Code (Source)	NDC:12213-832
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety			
Ingredient Name	Basis of Strength	Strength	
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	200 mL in 1 L	

Inactive Ingredients				
Ingredient Name	Strength			
Helium (UNII: 206GF3GB41)	800 mL in 1 L			

Packaging				
#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1 1	NDC:12213-832-13	382 L in 1 CYLINDER		
2 1	NDC:12213-832-58	561 L in 1 CYLINDER		
3 1	NDC:12213-832-12	5663 L in 1 CYLINDER		

Marketing Information				
Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date	
NADA	NADA141387	06/01/1996		

Labeler - NexAir, LLC (927024422)

Establishment			
Name	Address	ID/FEI	Business Operations
NexAir, LLC		792042108	manufacture

Establishment			
Name	Address	ID/FEI	Business Operations
NexAir, LLC		927024422	manufacture

Establishment			
Name	Address	ID/FEI	Business Operations
NexAir, LLC		844628334	manufacture

Revised: 7/2016 NexAir, LLC