


NITROUS OXIDE- nitrous oxide gas
Norco, Inc

NITROUS OXIDE USP LABEL


NITROUS OXIDE

UN1070

MEDICAL NITROUS OXIDE, USP




NON-FLAMMABLE GAS
2




OXIDIZER
5.1
(R-K14) 134527R

CONTENTS					
CYLINDER SIZE	WEIGHT	LITERS	CYLINDER SIZE	WEIGHT	LITERS
<input type="checkbox"/> G	56 LB.	13,796	<input type="checkbox"/> E	6 LB.	1,478
<input type="checkbox"/> M	28 LB.	6,898	<input type="checkbox"/> _____	_____	_____
<input type="checkbox"/> 20 LB.	20 LB.	4,927			



1125 W. Amity Road ■ Boise, ID 83705
208-336-1643

Rx Only. WARNING: Administration of Nitrous Oxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrous Oxide and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken. **DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY CAUSE DROWSINESS OR DIZZINESS. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY CAUSE FROSTBITE. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Avoid breathing gas. Do not get in eyes, on skin, or on clothing. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use. **FIRST AID: IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. **IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.



DO NOT REMOVE THIS PRODUCT LABEL

NITROUS OXIDE USP UN1070 MEDICAL NITROUS OXIDE, USP
NON-FLAMMABLE GAS 2 OXIDIZER 5.1 (R-K14) 134527R

CONTENTS

CYLINDER SIZE	WEIGHT	LITERS	CYLINDER SIZE	WEIGHT	LITERS
<input type="checkbox"/> G	56 LB.	13,796	<input type="checkbox"/> E	6 LB.	1,478
<input type="checkbox"/> M	28 LB.	6,898	<input type="checkbox"/> _____	_____	_____
<input type="checkbox"/> 20 LB.	20 LB.	4,927			

Rx only. WARNING: Administration of Nitrous Oxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrous Oxide and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects and the precautions to be taken. **DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER

PRESSURE; MAY EXPLODE IF HEATED. MAY CAUSE DROWSINESS OR DIZZINESS. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY CAUSE FROSTBITE. Do not handle until all safety precautions have been read and understood. Keep valves and fittings free from grease and oil. Avoid breathing gas. Do not get in eyes, on skin, or on clothing. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52° C (125° F). Read and follow the Safety Data Sheet (SDS) before use. FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

Norco

1125 W. Amity Road Boise, ID 83705

208-336-1643 DO NOT REMOVE THIS PRODUCT LABEL

res

NITROUS OXIDE				
nitrous oxide gas				
Product Information				
Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:42602-003	
Route of Administration	RESPIRATORY (INHALATION)			
Active Ingredient/Active Moiety				
Ingredient Name		Basis of Strength	Strength	
NITROUS OXIDE (UNII: K50XQU1029) (NITROUS OXIDE - UNII:K50XQU1029)		NITROUS OXIDE	99 L in 100 L	
Packaging				
#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:42602-003-01	1599 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/2008	
2	NDC:42602-003-02	4920 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/2008	
3	NDC:42602-003-03	13800 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/2008	
4	NDC:42602-003-04	246 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/2008	
5	NDC:42602-003-05	7380 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/2008	
6	NDC:42602-003-06	738 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/2008	
7	NDC:42602-003-07	2466 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/2008	

8	NDC:42602-003-08	370 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/2008	
9	NDC:42602-003-09	3700 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/2008	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA206009	09/01/2008	

Labeler - Norco, Inc (043694645)

Registrant - Norco, Inc (043694645)

Establishment

Name	Address	ID/FEI	Business Operations
Norco, Inc.		962460528	manufacture(42602-003)

Establishment

Name	Address	ID/FEI	Business Operations
Nitrous Oxide Corp		055761861	manufacture(42602-003)

Revised: 5/2024

Norco, Inc