

OXYGEN- oxygen gas
Wesco gas & Welding Supply Inc

Oxygen

OXYGEN, COMPRESSED USP

UN1072

PRODUCED BY AIR LIQUEFACTION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

CONTENTS:

LTRS:

CU.FT.

WESCO GAS & WELDING SUPPLY, INC.

WESCO GAS & WELDING SUPPLY, INC.

251-457-8681

Corporate Headquarters

940 N. M. L. King Drive

Prichard, AL 36610

www.wescoweld.com

NO SMOKING

NO VAPING



**OXYGEN, COMPRESSED USP
UN1072**

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. **DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.** Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

CONTENTS:

LTRS: CU.FT.

WESCO GAS & WELDING SUPPLY, INC.

WESCO GAS & WELDING SUPPLY, INC.

251-457-8681

Corporate Headquarters


940 N. M. L. King Drive

Prichard, AL 36610

www.wescoweld.com

NO SMOKING

NO VAPING



REFRIGERATED LIQUID
OXYGEN, REFRIGERATED LIQUID
UN1073

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.
DO NOT CHANGE OR FORCE FIT CONNECTIONS.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS;
MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH
OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only with equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Always keep container in upright position. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

WESCO GAS & WELDING SUPPLY, INC.

WESCO GAS & WELDING SUPPLY, INC.

251-457-8681

Corporate Headquarters

940 N. M. L. King Drive

Prichard, AL 36610

www.wescoweld.com

NO SMOKING

NO VAPING

REFRIGERATED LIQUID

**OXYGEN,
REFRIGERATED
LIQUID**

UN1073



**↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑
DO NOT CHANGE OR FORCE FIT CONNECTIONS.**

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.
CONTAINS REFRIGERATED GAS;
MAY CAUSE CRYOGENIC BURNS OR INJURY.
COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED
LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT.
Do not handle until all safety precautions have been read and
understood.
Keep and store away from clothing and other combustible
materials.
Keep valves and fittings free from grease and oil.
Use and store only outdoors or in a well-ventilated place.
Wear cold insulating gloves, face shield, and eye protection.
In case of fire: Stop leak if safe to do so.
Use a back flow preventive device in the piping.
Close valve after each use and when empty.
Use only with equipment rated for cylinder pressure.
Do not open valve until connected to equipment prepared for use.
Use only equipment of compatible materials of construction.
Open valve slowly.
Use only with equipment cleaned for oxygen service.
Always keep container in upright position.
DO NOT change or force fit connections.
Avoid spills.
Do not walk on or roll equipment over spills.
Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: **IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub
affected area. Get immediate medical advice/attention.

CAS: 7782-44-7
DO NOT REMOVE THIS PRODUCT LABEL.



**WESCO GAS &
WELDING SUPPLY, INC.**
CORPORATE HEADQUARTERS
640 N. M. L. King Drive
Prichard, AL 36810
251-457-8881
www.wescoweld.com



OXYGEN

oxygen gas

Product Information

Product Type	PRESCRIPTION ANIMAL DRUG	Item Code (Source)	NDC:52279-011
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	992 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:52279-011-01	34.7 L in 1 CYLINDER		
2	NDC:52279-011-02	97.0 L in 1 CYLINDER		
3	NDC:52279-011-03	141.4 L in 1 CYLINDER		
4	NDC:52279-011-04	161.4 L in 1 CYLINDER		
5	NDC:52279-011-05	197.7 L in 1 CYLINDER		
6	NDC:52279-011-06	234.1 L in 1 CYLINDER		
7	NDC:52279-011-07	390.9 L in 1 CYLINDER		

8	NDC:52279-011-08	554.5 L in 1 CYLINDER		
9	NDC:52279-011-09	643.2 L in 1 CYLINDER		
10	NDC:52279-011-10	1633.4 L in 1 CYLINDER		
11	NDC:52279-011-11	3271.8 L in 1 CYLINDER		
12	NDC:52279-011-12	7114.0 L in 1 CYLINDER		
13	NDC:52279-011-13	199.9 L in 1 CYLINDER		
14	NDC:52279-011-14	399.8 L in 1 CYLINDER		
15	NDC:52279-011-15	652.0 L in 1 CYLINDER		
16	NDC:52279-011-16	2537.6 L in 1 CYLINDER		
17	NDC:52279-011-17	3416.9 L in 1 CYLINDER		
18	NDC:52279-011-18	6632.7 L in 1 CYLINDER		
19	NDC:52279-011-19	9069.6 L in 1 CYLINDER		
20	NDC:52279-011-20	171959 L in 1 DEWAR		
21	NDC:52279-011-21	127580 L in 1 DEWAR		
22	NDC:52279-011-22	139334 L in 1 DEWAR		
23	NDC:52279-011-23	38062 L in 1 DEWAR		
24	NDC:52279-011-24	33984 L in 1 DEWAR		
25	NDC:52279-011-25	10195 L in 1 DEWAR		
26	NDC:52279-011-26	6796 L in 1 DEWAR		

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NADA	NADA141365	10/01/2002	

Labeler - Wesco gas & Welding Supply Inc (034091702)

Establishment

Name	Address	ID/FEI	Business Operations
Wesco Gas & Welding Supply Inc		034091702	manufacture

Revised: 10/2025

Wesco gas & Welding Supply Inc