OXYGEN - oxygen gas U.S. Oxygen and Supply, LLC

-----

#### **OXYGEN COMPRESSED USP SL**


OXYGEN COMPRESSED USP UN1072 OXYGEN 2 18033 (R 04/05)

WARNING: For emergency use only when administered by properly trained personnel for Oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of Oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for Oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

WARNING:HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Use in accordance with the Material Safety Data Sheet (MSDS). CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL

US Oxygen 3028 Abrams Arlington, TX 76010 (817) 652-9000



### REFRIGERATED OXYGEN LIQUID USP

REFRIGERATED LIQUID
OXYGEN REFRIGERATE LIQUID USP UN1073 OXYGEN 2

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. DO NOT CHANGE OR FORCE FIT CONNECTIONS.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING: EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION.

COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE OR IGNITION OR IMPACT.

CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away.

Use only with equipment cleaned for oxygen service.

Store and use with adequate ventilation.

Do not get liquid in eyes, on skin, or clothing.

For liquid withdraw, wear face shield and gloves.

Do not drop. Use suitable hand truck for container movement.

Avoid spills. Do not walk on or roll equipment over spills.

Cylinder temperature should not exceed 52° C (125° F).

Close valve after each use and when empty.

Use a back flow preventive device in the piping.

Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL

**US OXYGEN** 

3028 Abrams Arlington, TX 76010 (817) 652-9000

41533 (R 10/04)



VVI

# T ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. TO NOT CHANGE OR FORCE FIT CONNECTIONS.

WARNING:

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **R** only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

# Produced by Air Liquefaction.

WARNING:

EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER

PRESSURE.

VIGOROUSLY ACCELERATES COMBUSTION.

COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY

EXPLODE ON IGNITION OR IMPACT.
CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away.

Use only with equipment cleaned for oxygen service.

Store and use with adequate ventilation.

Do not get liquid in eyes, on skin, or clothing.

For liquid withdrawal, wear face shield and gloves.

Do not drop. Use suitable hand truck for container movement.

Avoid spills. Do not walk on or roll equipment over spills. Cylinder temperature should not exceed 52°C (125°F).

Close valve after each use and when empty.
Use a back flow preventive device in the piping.

Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.



## 3028 Abrams Arlington, TX 76010 (817) 652-9000

41533 (R 10/04)

#### **OXYGEN**

oxygen gas

**Product Information** 

Product Type HUMAN PRESCRIPTION DRUG

Item Code (Source)

NDC:54632-001

**Marketing End Date** 

Route of Administration

RESPIRATORY (INHALATION)

**Active Ingredient/Active Moiety** 

Ingredient Name
Basis of Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)
OXYGEN (UNII: S88TT14065) OXYGEN 99 L in 100 L

Packaging				
#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:54632-001-01	420 L in 1 CYLINDER		
2	NDC:54632-001-02	690 L in 1 CYLINDER		
3	NDC:54632-001-03	3160 L in 1 CYLINDER		
4	NDC:54632-001-04	7060 L in 1 CYLINDER		
5	NDC:54632-001-05	8510 L in 1 CYLINDER		
6	NDC:54632-001-06	113.3 L in 1 CYLINDER		
7	NDC:54632-001-07	164.5 L in 1 CYLINDER		
8	NDC:54632-001-08	139 L in 1 CYLINDER		
9	NDC:54632-001-09	248.4 L in 1 CYLINDER		
10	NDC:54632-001-10	647.1 L in 1 CYLINDER		
11	NDC:54632-001-11	1723.6 L in 1 CYLINDER		
12	NDC:54632-001-12	160 L in 1 DEWAR		
13	NDC:54632-001-13	180 L in 1 DEWAR		
14	NDC:54632-001-14	230 L in 1 DEWAR		
15	NDC:54632-001-15	240 L in 1 DEWAR		

Marketing Information				
Marketing Category	Application Number or Monograph Citation	Marketing Start Date		

NDA	NDA206023	11/15/20 12	

## Labeler - U.S. Oxygen and Supply, LLC (944782804)

## Registrant - U.S. Oxygen and Supply, LLC (944782804)

Establishment				
Name	Address	ID/FEI	Business Operations	
U.S. Oxygen and Supply, LLC		944782804	manufacture (54632-001)	

Establishment				
Name	Address	ID/FEI	Business Operations	
AIRGAS USA, LLC		791526940	manufacture(54632-001)	

Revised: 2/2014 U.S. Oxygen and Supply, LLC