

OXYGEN- oxygen gas
United States Cylinder Gas Corporation

oxygen

OXYGEN, COMPRESSED USP
UN1072

PRODUCED BY AIR LIQUEFACTION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

US GAS

United States Cylinder Gas

11618 South Mayfield Alsip, IL 60803 (708) 389-1402

NO SMOKING

NO VAPING



REFRIGERATED LIQUID
OXYGEN, REFRIGERATED LIQUID USP

UN1073

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

DO NOT CHANGE OR FORCE FIT CONNECTIONS.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.

CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY.

COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT.

Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use only outdoors or with adequate ventilation. Store in a well-ventilated place. Wear cold insulating gloves and either face shield or eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical help.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

US GAS

United States Cylinder Gas

11618 South Mayfield Alsip, IL 60803

(708) 389-1402

NO SMOKING

NO VAPING

REFRIGERATED LIQUID

**OXYGEN,
REFRIGERATED
LIQUID
USP
UN1073**



**1 ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. 1
DO NOT CHANGE OR FORCE FIT CONNECTIONS.**

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx required.**

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.
CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY
COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT.

Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use only outdoors or with adequate ventilation. Store in a well-ventilated place. Wear cold insulating gloves and either face shield or eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: **IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical help.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.



USGas
United States Cylinder Gas
11618 South Mayfield • Alsip, IL 60803
(708) 389-1402



OXYGEN

oxygen gas

Product Information

Product Type	PRESCRIPTION ANIMAL DRUG	Item Code (Source)	NDC:68877-011
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:68877-011-01	7108 L in 1 CYLINDER		
2	NDC:68877-011-02	3540 L in 1 CYLINDER		
3	NDC:68877-011-03	2266 L in 1 CYLINDER		
4	NDC:68877-011-04	1133 L in 1 CYLINDER		
5	NDC:68877-011-05	680 L in 1 CYLINDER		
6	NDC:68877-011-06	396 L in 1 CYLINDER		
7	NDC:68877-011-07	594 L in 1 CYLINDER		

8	NDC:68877-011-08	160 L in 1 CYLINDER		
9	NDC:68877-011-09	200 L in 1 CYLINDER		
10	NDC:68877-011-10	240 L in 1 CYLINDER		
11	NDC:68877-011-11	184372 L in 1 DEWAR		
12	NDC:68877-011-12	141945 L in 1 DEWAR		
13	NDC:68877-011-13	127934 L in 1 DEWAR		

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NADA	NADA141387	05/25/2004	

Labeler - United States Cylinder Gas Corporation (825010051)

Establishment

Name	Address	ID/FEI	Business Operations
United States Cylinder Gas Corporation		825010051	manufacture

Revised: 10/2025

United States Cylinder Gas Corporation