

OXYGEN- oxygen gas
JW Welding Supplies & Tools

OXYGEN USP LABEL

OXYGEN,
COMPRESSED
USP

UN 1072

JW9 OXYGEN 2

JW Welding Supply

FALLON, NV 89406

(775)423-4774


WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. **Produced by Air Liquefaction.****DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125° F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 **DO NOT REMOVE THIS PRODUCT LABEL.**

Lot#: **NET CONTENTS:**



**OXYGEN,
COMPRESSED
USP
UN 1072**

JW Welding Supply
FALLON, NV 89406
(775) 423-4774




WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only.** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by **Air Liqefaction.**

DANGER: MAY CAUSE OR INTENSIFY FIRE: OXIDIZER. CONTAINS GAS UNDER PRESSURE. MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7 **DO NOT REMOVE THIS PRODUCT LABEL**

NET CONTENTS:



OXYGEN REFRIGERATED LABEL

**Oxygen,
Refrigerated
Liquid, USP**



UN 1073 Rx ONLY

Gross Wt.	lbs.	oz.
Net Wt.	lbs.	oz.
Size	Contents	Liters

Rx ONLY. WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation

by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by **Air Liquefaction**. **DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.** Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. **DO NOT** change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use. **FIRST AID: IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. **CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL**



JW Welding Supply
FALLON, NV 89406
(775) 423-4774



Oxygen, Refrigerated Liquid, U.S.P.

OXYGEN 2

UN 1073 Rx ONLY

Gross Wt. lbs. oz.

Net Wt. lbs. oz.

Size Contents Liters

Rx ONLY. WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction of resuscitative equipment.

Produced by Air Liquefaction. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDER, CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only the equipment of compatible materials equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position.

Read and follow the Safety Data Sheet (SDS) before use. **FIRST AID FIRST AID: IF ON SKIN:** Thaw affected parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. CAS: 7782-44-7 **DO NOT REMOVE THIS PRODUCT LABEL**

JW Welding Supply

FALLON, NV 89406

(775)423-4774

JW-4

A16

**Oxygen,
Refrigerated
Liquid, USP**



UN 1073 Rx ONLY

Gross Wt.	lbs.	oz.
Net Wt.	lbs.	oz.
Size	Contents	Liters

Rx ONLY. WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by **Air Liquefaction. DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use. **FIRST AID: IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. CAS: 7782-44-7 **DO NOT REMOVE THIS PRODUCT LABEL**





JW Welding Supply
 FALLON, NV 89406
 (775) 423-4774



OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:59336-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:59336-001-01	3539 L in 1 CYLINDER; Type 0: Not a Combination Product	12/12/2013	
2	NDC:59336-001-02	7985 L in 1 CYLINDER; Type 0: Not a Combination Product	12/12/2013	
3	NDC:59336-001-03	165 L in 1 CYLINDER; Type 0: Not a Combination Product	12/12/2013	
4	NDC:59336-001-04	193 L in 1 CYLINDER; Type 0: Not a Combination Product	12/12/2013	
5	NDC:59336-001-05	248 L in 1 CYLINDER; Type 0: Not a Combination Product	12/12/2013	
6	NDC:59336-001-06	396 L in 1 CYLINDER; Type 0: Not a Combination Product	12/12/2013	
7	NDC:59336-001-07	651 L in 1 CYLINDER; Type 0: Not a Combination Product	12/12/2013	
8	NDC:59336-001-08	137616 L in 1 DEWAR; Type 0: Not a Combination Product	12/12/2013	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205767	12/12/2013	

Labeler - JW Welding Supplies & Tools (102836251)

Registrant - JW Welding Supplies & Tools (102836251)

Establishment

Name	Address	ID/FEI	Business Operations
JW Welding Supplies & Tools		102836251	manufacture(59336-001)

Establishment

Name	Address	ID/FEI	Business Operations
Linde LLC		102835006	manufacture(59336-001)

Revised: 10/2019

JW Welding Supplies & Tools