

OXYGEN- oxygen gas
Alliance Welding Supplies, Inc.

Oxygen

ALLIANCE Welding Supplies 1224 SIXTH St. . BERKELEY, CA 94710 88-414-6363


OXYGEN, COMPRESSED USP UN1072

DO NOT REMOVE THIS PRODUCT LABEL OXYGEN 2

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. PRODUCED BY AIR LIQUIFACTION
DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7

Pressure PSIG at 70 degrees F Size Contents Liters



REFRIGERATED LIQUID OXYGEN, REFRIGERATED LIQUID USP UN1073 OXYGEN 2
CONTENTS: LTRS: CU FT:

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be filled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS REFRIGERATED GAS;
MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID

OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills, Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

ALLIANCE Welding Supplies 1224 SIXTH St. . BERKELEY, CA 94710 88-414-6363

REFRIGERATED LIQUID

**OXYGEN,
REFRIGERATED
LIQUID
USP
UN1073**



CONTENTS: _____

LTRS:
CU FT:

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act. **Produced by Air Liquefaction.**

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. **DO NOT** change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.
CAS: 7782-44-7



DO NOT REMOVE THIS PRODUCT LABEL

 **ALLIANCE**
Welding Supplies
1224 SIXTH ST. • BERKELEY, CA 94710 47133
888-414-6363 (01/15)

OXYGEN

oxygen gas

Product Information

Product Type	PRESCRIPTION ANIMAL DRUG	Item Code (Source)	NDC:50562-011
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	992 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:50562-011-01	34 L in 1 CYLINDER		
2	NDC:50562-011-02	97 L in 1 CYLINDER		
3	NDC:50562-011-03	141 L in 1 CYLINDER		
4	NDC:50562-011-04	161 L in 1 CYLINDER		
5	NDC:50562-011-05	197 L in 1 CYLINDER		
6	NDC:50562-011-06	234 L in 1 CYLINDER		
7	NDC:50562-011-07	390 L in 1 CYLINDER		
8	NDC:50562-011-08	554 L in 1 CYLINDER		
9	NDC:50562-011-09	643 L in 1 CYLINDER		
10	NDC:50562-011-10	1633 L in 1 CYLINDER		
11	NDC:50562-011-11	3271 L in 1 CYLINDER		
12	NDC:50562-011-12	7114 L in 1 CYLINDER		
13	NDC:50562-011-13	199 L in 1 CYLINDER		
14	NDC:50562-011-14	399 L in 1 CYLINDER		
15	NDC:50562-011-15	652 L in 1 CYLINDER		
16	NDC:50562-011-16	2537 L in 1 CYLINDER		
17	NDC:50562-011-17	3416 L in 1 CYLINDER		
18	NDC:50562-011-18	6632 L in 1 CYLINDER		
19	NDC:50562-011-19	8569 L in 1 CYLINDER		
20	NDC:50562-011-20	9069 L in 1 CYLINDER		
21	NDC:50562-011-21	127425 L in 1 CYLINDER		
22	NDC:50562-011-22	142150 L in 1 CYLINDER		

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NADA	NADA141365	06/01/2009	

Labeler - Alliance Welding Supplies, Inc. (029292513)**Establishment**

Name	Address	ID/FEI	Business Operations
Alliance Welding Supplies, Inc.		961655144	manufacture