

OXYGEN- oxygen gas
Super Gas, Inc.

Oxygen

OXYGEN, COMPRESSED USP

UN1072

PRODUCED BY AIR LIQUEFACTION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valves slowly. Use only with equipment cleaned for oxygen service. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

WANGER WELDING SUPPLY

10 GAY STREET LONGMONT, CO 80501

303-776-1491

CONTENTS: LTRS CU.FT.

NO SMOKING

NO VAPING



OXYGEN, COMPRESSED USP

UN1072

Produced by Air Liquefaction

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

Do not handle until all safety precautions have been read and understood. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

NO SMOKING

NO VAPING

WAGNER WELDING SUPPLY

10 GAY STREET LONGMONT, CO 80501

303-776-1491

**OXYGEN,
COMPRESSED
USP**

UN1072



Produced by Air Liquefaction

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **is required.**

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

Do not handle until all safety precautions have been read and understood. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

**NO SMOKING
NO VAPING**



WAGNER WELDING SUPPLY

10 GAY STREET • LONGMONT, CO 80501
303-776-1491

40035
(01/25)

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:61128-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	992 L in 1000 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:61128-001-01	8080 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	12/31/2022
2	NDC:61128-001-02	4040 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	12/31/2022
3	NDC:61128-001-03	2380 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	12/31/2022
4	NDC:61128-001-04	705 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	12/31/2022

5	NDC:61128-001-05	425 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	12/31/2022
6	NDC:61128-001-06	212 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	12/31/2022
7	NDC:61128-001-07	129280 L in 1 DEWAR; Type 0: Not a Combination Product	12/01/2007	12/31/2022
8	NDC:61128-001-08	120327 L in 1 DEWAR; Type 0: Not a Combination Product	12/01/2007	12/31/2022
9	NDC:61128-001-09	30935 L in 1 DEWAR; Type 0: Not a Combination Product	12/01/2007	12/31/2022
10	NDC:61128-001-10	420 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	
11	NDC:61128-001-11	690 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	
12	NDC:61128-001-12	3160 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	
13	NDC:61128-001-13	6270 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	
14	NDC:61128-001-14	180 L in 1 DEWAR; Type 0: Not a Combination Product	12/01/2007	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205712	12/01/2007	

Labeler - Super Gas, Inc. (832100437)

Establishment

Name	Address	ID/FEI	Business Operations
Super Gas, Inc.		832100437	manufacture(61128-001)

Revised: 11/2025

Super Gas, Inc.