

**OXYGEN- oxygen gas**  
**Super Gas, Inc.**

-----  
**Oxygen**

OXYGEN, COMPRESSED USP

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. DANGER: MAY CAUSE OR INTENSIFY FIRE: OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a backflow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52C (125F). Read and follow the Safety Data Sheet (SDS) before use.

CAS 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

WAGNER WELDING SUPPLY 10 GAY STREET LONGMONT, CO 80501 303-776-1491

CONTENTS: LTRS CU. FT.


UN1072

PRODUCED BY AIR LIQUEFACTION

OXYGEN 2

17033 (12/14)

PICTOGRAM GHS04 GAS CYLINDER



OXYGEN, REFRIGERATED LIQUID USP UN1073

OXYGEN 2

Rx only

**WARNING:** For emergency use only when administered by properly administered personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

Produced by Air Liquefaction.

**DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.** Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold-insulating gloves, face shield and eye protection. In case of fire: Stop leak if safe to do so. Use a back-flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. **DO NOT** change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use. **FIRST AID: IF ON SKIN:** thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate advice/attention. CAS: 7782-44-7

**DO NOT REMOVE THIS PRODUCT LABEL.**

**WAGNER WELDING SUPPLY 10 GAY STREET LONGMONT, CO 80501**

**303-776-1491**

**41550 (12/14)**

**PICTOGRAM GHS04 GAS CYLINDER**

**OXYGEN,  
REFRIGERATED  
LIQUID  
USP  
UN1073**



**R<sub>x</sub> only**

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **R<sub>x</sub> only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.  
Produced by Air Liquefaction.

**DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use. **FIRST AID: IF ON SKIN:** thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. CAS: 7782-44-7



DO NOT REMOVE THIS PRODUCT LABEL.

**WAGNER WELDING SUPPLY**  
10 GAY STREET • LONGMONT, CO 80501  
303-776-1491

41550 (12/14)

OXYGEN, COMPRESSED USP

UN1072

OXYGEN 2

PRODUCED BY AIR LIQUEFACTION

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **R<sub>x</sub> only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

**DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors


or in well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52C (125F). Read and follow the Safety Data Sheets (0) before use. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

WAGNER WELDING SUPPLY 10 GAY STREET LONGMONT, CO 80501 303-776-1491

**OXYGEN,  
COMPRESSED  
USP**

**UN1072**

**Produced by Air Liquefaction**




**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal *Food, Drug, and Cosmetic Act*.

**DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet (0) before use.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.



**WAGNER WELDING SUPPLY**  
10 GAY STREET • LONGMONT, CO 80501  
303-776-1491

40035  
(01/15)

# OXYGEN

oxygen gas

## Product Information

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:61128-001
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

## Active Ingredient/Active Moiety

<b>Ingredient Name</b>	<b>Basis of Strength</b>	<b>Strength</b>
<b>OXYGEN</b> (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	992 L in 1000 L

## Packaging

<b>#</b>	<b>Item Code</b>	<b>Package Description</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
1	NDC:61128-001-01	8080 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	12/31/2022
2	NDC:61128-001-02	4040 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	12/31/2022
3	NDC:61128-001-03	2380 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	12/31/2022
4	NDC:61128-001-04	705 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	12/31/2022
5	NDC:61128-001-05	425 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	12/31/2022
6	NDC:61128-001-06	212 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	12/31/2022
7	NDC:61128-001-07	129280 L in 1 DEWAR; Type 0: Not a Combination Product	12/01/2007	12/31/2022
8	NDC:61128-001-08	120327 L in 1 DEWAR; Type 0: Not a Combination Product	12/01/2007	12/31/2022
9	NDC:61128-001-09	30935 L in 1 DEWAR; Type 0: Not a Combination Product	12/01/2007	12/31/2022
10	NDC:61128-001-10	420 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	
11	NDC:61128-001-11	690 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	
12	NDC:61128-001-12	3160 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	
13	NDC:61128-001-13	6270 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2007	
14	NDC:61128-001-14	180 L in 1 DEWAR; Type 0: Not a Combination Product	12/01/2007	

## Marketing Information

<b>Marketing Category</b>	<b>Application Number or Monograph Citation</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
NDA	NDA205712	12/01/2007	

**Labeler** - Super Gas, Inc. (832100437)

**Establishment**

<b>Name</b>	<b>Address</b>	<b>ID/FEI</b>	<b>Business Operations</b>
Super Gas, Inc.		832100437	manufacture(61128-001)

Revised: 12/2024

Super Gas, Inc.