OXYGEN- oxygen gas South Jersey Welding Supply

Oxygen HP Label
OXYGEN,
COMPRESSED
USP UN 1072
Produced by Air Liquefaction
OXYGEN 2
18035 (07/17)

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. **DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a backflow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125° F). Read and follow the Safety Data Sheet (SDS) before use.

SOUTH JERSEY WELDING SUPPLY

94 W FOREST GROVE RD VINELAND, MJ 08360 • 856-778-4440 CAS 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.



Oxygen Refrigerated Liq Label REFRIGERATED LIQUID

OXYGEN REFRIGERATED LIQUID USP UN1073 OXYGEN 2

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children.

Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacture in accordance with the Federal Food, Drug, and Cosmetic Act.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE: OXIDIZER. CONTAINS REFRIGERATED GAS: MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak of safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of consruction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advise/attention.

CAS: 7782-44-7

DO NOT REOVE THIS PRODUCT LABEL

SOUTH IERSEY WELDING SUPPLY

94 W FOREST GROVE RD VINELAND, NJ 08360 • 856-778-4440 41533 (01/15)



WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, R, only.

> Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children

> Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

Produced by Air Liquefaction.

UANGER: MAY GAUSE UK IN LENSIFY FIRE; UXIDIZER, CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT

> Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL



SOUTH JERSEY WELDING SUPPLY

94 W FOREST GROVE RD VINELAND, NJ 08360 • 856-778-4440

> 41533 (01/15)

OXYGEN

oxygen gas

Prod	luct	Infor	mation

Item Code (Source) NDC:11056-001 **Product Type HUMAN PRESCRIPTION DRUG Route of Administration** RESPIRATORY (INHALATION)

Active	Ingredient/Active	Moietv
ACCITC	iligi calcili, Active	1-10101

ı	Active ingredient/Active Molety				
	Ingredient Name	Basis of Strength	Strength		
	OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L		

Pā	Packaging				
#	Item Code	Package Description	Marketing Start Date	Marketing End Date	
1	NDC:11056- 001-01	169 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1962		
2	NDC:11056- 001-02	254 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1962		
3	NDC:11056- 001-03	311 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1962		
4	NDC:11056- 001-04	623 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1962		
5	NDC:11056- 001-05	566 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1962		
6	NDC:11056- 001-06	2265 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1962		
7	NDC:11056- 001-07	3455 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1962		
8	NDC:11056- 001-08	4361 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1962		
9	NDC:11056- 001-09	7051 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1962		
10	NDC:11056- 001-10	9543 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1962		
11	NDC:11056- 001-11	127440 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1962		
12	NDC:11056- 001-12	250971 L in 1 TANK; Type 0: Not a Combination Product	01/01/1962		
13	NDC:11056- 001-13	112 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1962		

Marketing Information				
Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date	
NDA	NDA205849	01/01/1962		

Labeler - South Jersey Welding Supply (796071926)

Registrant - South Jersey Welding Supply (796071926)

Establishment				
Name	Address	ID/FEI	Business Operations	
THORNTON ENTERPRISES INC		796071926	manufacture(11056-001)	