OXYGEN- oxygen gas DJB Gas Services, Inc

Oxygen

OXYGEN, COMPRESSED, USP UN1072

OXYGEN 2

WARNING: For emergency use only when administered properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of constructions and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect form sunlight when ambient temperature exceeds 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL

DJB Gas Services, Inc.

DJB GAS SERVICES, INC. 1177 South Swaner Road Salt Lake City, Utah 84104 801-908-7800 www.djbgas.com

CONTENTS: LTRS CU. FT.



OXYGEN REFRIGERATED LIQUID, USP UN1073 OXYGEN 2 ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

WARNING USP For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills, Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. Lot Number: Contents: Expiration Date: DO NOT REMOVE THIS PRODUCT LABEL.





PRINTED BY RATERMANN MFG., INC.

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

WARNING

USP

For emergency use only when administered by property trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only.**

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction. Keep out of reach of children; and Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal *Food*, *Drug, and Cosmetic Act*.

CAS: 7782-44-7

DANGER

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a wellwenflatted pictore. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the spiring. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment deemed for oxygen service. Do NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position.



FIRST AID IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

Lot Number: Contents: Expiration Date:

DO NOT REMOVE THIS PRODUCT LABEL

READ AND FOLLOW THE SAFETY DATA SHEET (SDS) BEFORE USE.

OXYGEN, REFRIGERATED LIQUID USP UN1073 OXYGEN 2

DJB Gas Services, Inc. DJB GAS SERVICES, INC. 1177 South Swaner Road Salt Lake City, Utah 84104

801-908-7800 . www.djbgas.com

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills, Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL. CAS: 7782-44-7



OXYGEN

oxygen gas

| Product Information | | | |
|-------------------------|--------------------------|--------------------|---------------|
| Product Type | HUMAN PRESCRIPTION DRUG | ltem Code (Source) | NDC:43621-001 |
| Route of Administration | RESPIRATORY (INHALATION) | | |

| Active Ingredient/Active Moiety | | | |
|---|--------------------------|---------------|--|
| Ingredient Name | Basis of Strength | Strength | |
| OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065) | OXYGEN | 990 mL in 1 L | |

| Packaging | | | | |
|-----------|----------------------|---|-------------------------|-----------------------|
| # | ltem Code | Package Description | Marketing Start Date | Marketing End Date |
| 1 | NDC:43621- 001-11 | 198 L in 1 CYLINDER; Type 0: Not a Combination Product | 01/01/1990 | |
| 2 | NDC:43621- 001-12 | 255 L in 1 CYLINDER; Type 0: Not a Combination Product | 01/01/1990 | |
| 3 | NDC:43621- 001-13 | 425 L in 1 CYLINDER; Type 0: Not a Combination Product | 01/01/1990 | |
| 4 | NDC:43621- 001-14 | 708 L in 1 CYLINDER; Type 0: Not a Combination Product | 01/01/1990 | |
| 5 | NDC:43621- 001-15 | 1133 L in 1 CYLINDER; Type 0: Not a Combination Product | 01/01/1990 | |
| 6 | NDC:43621- 001-16 | 1614 L in 1 CYLINDER; Type 0: Not a Combination Product | 01/01/1990 | |
| | | | | |

| ND. | A | NDA205712 | 01/01/1990 | | |
|-----------------------|-----------------------|---|-------------------------|-----------------------|--|
| | Marketing Category | Application Number or Monograph Citation | Marketing Start Date | Marketing End Date | |
| Marketing Information | | | | | |
| | | | | | |
| 11 | NDC:43621- 001-21 | 180 L in 1 DEWAR; Type 0: Not a Combination Product | 01/01/1990 | | |
| 10 | NDC:43621- 001-20 | 9543 L in 1 CYLINDER; Type 0: Not a Combination Product | 01/01/1990 | | |
| 9 | NDC:43621- 001-19 | 7108 L in 1 CYLINDER; Type 0: Not a Combination Product | 01/01/1990 | | |
| 8 | NDC:43621- 001-18 | 3539 L in 1 CYLINDER; Type 0: Not a Combination Product | 01/01/1990 | | |
| 7 | NDC:43621- 001-17 | 2265 L in 1 CYLINDER; Type 0: Not a Combination Product | 01/01/1990 | | |

Labeler - DJB Gas Services, Inc (053129180)

| Establishment | | | | | |
|-----------------------|---------|-----------|----------------------------|--|--|
| Name | Address | ID/FEI | Business Operations | | |
| DJB Gas Services, Inc | | 053129180 | manufacture(43621-001) | | |

Revised: 10/2024

DJB Gas Services, Inc