

OXYGEN- oxygen gas
Hagan, Logan Welding Supply Inc

oxygen

OXYGEN, COMPRESSED LIQUID USP UN1072 DO NOT REMOVE THIS PRODUCT LABEL.

OXYGEN 2 815033 (08/04)

WARNING: For emergency use only when administered by properly trained personnel

for oxygen deficiency and resuscitation. For all other medical applications, Rx

only.

CAUTION: Federal law prohibits dispensing without prescription. Uninterrupted

use of high concentrations of oxygen over a long duration, without monitoring

its effect on oxygen content of arterial blood, may be harmful. Use only with

pressure reducing equipment and apparatus designed for oxygen. Do not attempt to

use on patients who have stopped breathing, unless used in conjunction with

resuscitative equipment. Produced by Air Liquefaction.

WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep

oil, grease away. Open valve slowly. Store and use with adequate ventilation.

Use only with equipment cleaned for oxygen service and rated for cylinder

pressure. Use back flow preventive device in the piping. Close valve after each

use and when empty. Cylinder temperature should not exceed 52C (125F). Use in

accordance with the Material Safety Data Sheets (MSDS).

CAS: 7782-44

-7

DO NOT REMOVE THIS PRODUCT LABEL

LOGAN HAGAN WELDING SUPPLY INC.

303 N Zetterower Ave. Statesboro, GA 30459



912-764-6481

OXYGEN, COMPRESSED LIQUID USP UN1072 DO NOT REMOVE THIS PRODUCT LABEL.

OXYGEN 2 815033 (08/04)

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.

CAUTION: Federal law prohibits dispensing without prescription. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with

resuscitative equipment. Produced by Air Liquefaction.

WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep

oil, grease away. Open valve slowly. Store and use with adequate ventilation.

Use only with equipment cleaned for oxygen service and rated for cylinder pressure. Use back flow preventive device in the piping. Close valve after each

use and when empty. Cylinder temperature should not exceed 52C (125F). Use in accordance with the Material Safety Data Sheets (MSDS). CAS: 7782-44

DO NOT REMOVE THIS PRODUCT LABEL
 LOGAN HAGAN WELDING SUPPLY INC.
 303 N Zetterower Ave. Statesboro, GA 30459



912-764-6481

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:49507-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	995 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:49507-001-01	170 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1977	
2	NDC:49507-001-02	380 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1977	
3	NDC:49507-001-03	662 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1977	
4	NDC:49507-001-04	3454 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1977	
5	NDC:49507-001-05	6909 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1977	
6	NDC:49507-001-06	30 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1977	
7	NDC:49507-001-07	45 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1977	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA206023	01/01/1977	

Labeler - Hagan, Logan Welding Supply Inc (033847066)

Establishment

Name	Address	ID/FEI	Business Operations
Hagan, Logan Welding Supply Inc		033874066	manufacture(49507-001)

Revised: 10/2021

Hagan, Logan Welding Supply Inc