

**OXYGEN- oxygen gas**  
**A&B Welding Supply, LLC**

-----  
**Oxygen Labels**

OXYGEN, COMPRESSED USP

UN1072

PRODUCED BY AIR LIQUEFACTION

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

**DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

AB WELDING SUPPLY

914 East Chicago Street

Rapid City, SD 57701

605-674-7523

NO SMOKING

NO VAPING

CONTENTS: LTRS: CU.FT.



OXYGEN, COMPRESSED USP

UN1072

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

AB WELDING SUPPLY

914 East Chicago Street

Rapid City, SD 57701

605-674-7523

NO SMOKING

NO VAPING

CONTENTS: LTRS: CU.FT.



OXYGEN, COMPRESSED USP

UN1072

C.A.S. NO. 7782-44-7

Contents LTRS. CU.FT.

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

**DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

DO NOT REMOVE THIS PRODUCT LABEL.

AB WELDING SUPPLY

914 East Chicago Street

Rapid City, SD 57701

605-674-7523

NO SMOKING

NO VAPING

**OXYGEN,  
COMPRESSED  
USP  
UN 1072**  
C.A.S. NO. 7782-44-7

Contents \_\_\_\_\_ LTRS.   
CU. FT.

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx required.** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

**DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use.

DO NOT REMOVE THIS PRODUCT LABEL.

**AB**  
WELDING  
SUPPLY

914 East Chicago Street  
Rapid City, SD 57701  
605-674-7523

 

**OXYGEN**  
2  
(R-K20) 115832R

REFRIGERATED LIQUID

OXYGEN, REFRIGERATED LIQUID USP

UN1073

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

DO NOT CHANGE OR FORCE FIT CONNECTIONS.

CONTENTS: LTRS: CU.FT.

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

**DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT.

Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use only outdoors or with adequate ventilation. Store in a well-ventilated place. Wear cold



oxygen gas

**Product Information**

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:55728-100
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

**Active Ingredient/Active Moiety**

<b>Ingredient Name</b>	<b>Basis of Strength</b>	<b>Strength</b>
<b>OXYGEN</b> (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	990 mL in 1 L

**Packaging**

<b>#</b>	<b>Item Code</b>	<b>Package Description</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
1	NDC:55728-100-01	8070 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
2	NDC:55728-100-02	7050 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
3	NDC:55728-100-03	4360 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
4	NDC:55728-100-04	2350 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
5	NDC:55728-100-05	3284 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
6	NDC:55728-100-06	170 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
7	NDC:55728-100-07	124 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
8	NDC:55728-100-08	164 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
9	NDC:55728-100-09	425 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
10	NDC:55728-100-10	622 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
11	NDC:55728-100-11	160 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
12	NDC:55728-100-12	196 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
13	NDC:55728-100-13	618893 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
14	NDC:55728-100-14	248 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
15	NDC:55728-100-15	589 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
16	NDC:55728-100-16	646 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	

**Marketing Information**

<b>Marketing Category</b>	<b>Application Number or Monograph Citation</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
NDA	NDA205767	01/02/1978	

**Labeler** - A&B Welding Supply, LLC (007499460)

**Registrant** - A&B Welding Supply, LLC (007499460)

**Establishment**

<b>Name</b>	<b>Address</b>	<b>ID/FEI</b>	<b>Business Operations</b>
A&B Welding Supply, LLC		007499460	manufacture(55728-100)

Revised: 11/2025

A&B Welding Supply, LLC