## NITROGEN- nitrogen gas A & B Welding Supply Co.

-----

## **Nitrogen**

NITROGEN, Refrigerated Liquid UN1977 CAS 7727-37-9 NON-FLAMMABLE GAS 2

Nitrogen, NF

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION DO NOT CHANGE OR FORCE FIT CONNECTIONS.

WARNING: EXTREMELY COLD LIQUID AND GAS UNDER PRESSURE.

CAN CAUSE RAPID SUFFOCATION.

CAN CAUSE SEVERE FROSTBITE.

Store and use with adequate ventilation.

Do not get liquid in eyes, on skin or clothing.

For liquid withdrawal, wear face shield and gloves.

Do not drop. Use hand truck for container movement.

Container temperature should not exceed 52oC(125oF).

Close valve after each use and when empty.

Use a back flow preventive device in the piping.

Use in accordance with Material Safety Data Sheet.

FIRST AID: IF INHALED, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

IN CASE OF FROSTBITE, obtain medical treatment immediately.

Rx Only

WARNING: Administration of nitrogen may be hazardous or contraindicated. For use by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

DO NOT REMOVE THIS LABEL.

A and B Welding Supply Co. Inc. 605-343-5365 914 East Chicago Street PO Box 2053 NITROGEN, Refrigerated Liquid
UN1977
CAS 7727-37-9

NON-FLAMMABLE
GAS
2

### Nitrogen, NF

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION DO NOT CHANGE OR FORCE FIT CONNECTIONS.

WARNING: EXTREMELY COLD LIQUID AND GAS UNDER PRESSURE.

CAN CAUSE RAPID SUFFOCATION.

CAN CAUSE SEVERE FROSTBUTE.

Store and use with adequate ventilation.

Do not get liquid in eyes, on skin or clothing.

For liquid withdrawal, wear face shield and gloves.

Do not drop. Use hand truck for container movement.

Container temperature should not exceed \$2°C(125°F).

Close valve after each use and when empty.

Use a back flow preventive device in the piping.

Use in accordance with Material Safety Data Sheet.

FIRST AID: IF INHALED, remove to fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen. Call a physician.

IN CASE OF FROSTBITE, obtain medical treatment immediately.

Rx Only

WARNING: Administration of nitrogen may be hazardous or contraindicated. For use by or under the supervision of a licensed practitioner who is experienced in the

or under the supervision of a licensed, practitioner who is expenseded in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the

precautions to be taken.

DO NOT REMOVE THIS LABEL.

A & B Welding Supply Co. Inc.

605-343-5365 914 East Chicago Street PO Box 2053 Rapid City, SD 57709

Contents:	60.5
-----------	------

Rapid City, SD 57709 Contents:

NITROGEN, COMPRESSED NF UN 1066 NON-FLAMMABLE GAS 2

Rx only. WARNING: Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and precautions to be taken. WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Use a back flow preventive device in the piping. Use only with equipment rated for cylinder pressure. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceed 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet (SDS) before use. FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention. CAS: 7727-37-9 DO NOT REMOVE THIS PRODUCT LABEL.

A&B Welding Supply Co., Inc.

914 W Chicago Street

Rapid City, SD 57701 605-343-5365 CONTENTS: LTRS CU FT



FILLED AND DISTRIBUTED BY:

A AND B WELDING SUPPLY CO., INC

914 E CHICAGO ST

RAPID CITY, SD 57701

605-343-5365

NITROGEN, REFRIGERATED LIQUID NF

UN 1977

NON-FLAMMABLE GAS 2

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

DO NOT CHANGE OR FORCE FIT CONNECTIONS

Rx only. WARNING: Administration of Nitrogen my be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects and the precautions to be taken.

WARNING: EXTREMELY COLD LIQUID AND GAS UNDER PRESSURE. CAN CAUSE RAPID SUFFOCATION. CAN CAUSE SEVERE FROSTBITE. Store and use with adequate ventilation. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. cylinder temperature should not exceed 52 degrees C (125 degrees F). Close valve after each use and when empty. Use a back flow preventive device in the piping. Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IF INHALED, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give Oxygen. Call a physician. IN CASE OF FROSTBITE, obtain medical treatment immediately. CAS 7727-37-9



#### **NITROGEN**

nitrogen gas

Product Information			
Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:55728-200
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety			
Ingredient Name	<b>Basis of Strength</b>	Strength	
NITROGEN (UNII: N762921K75) (NITROGEN - UNII:N762921K75)	NITROGEN	990 mL in 1 L	

Pa	Packaging				
#	Item Code	Package Description	Marketing Start Date	Marketing End Date	
1	NDC:55728- 200-01	5 L in 1 CYLINDER; Type 0: Not a Combination Product	01/09/2012		
2	NDC:55728- 200-02	10 L in 1 CYLINDER; Type 0: Not a Combination Product	01/09/2012		
3	NDC:55728- 200-03	18 L in 1 CYLINDER; Type 0: Not a Combination Product	01/09/2012		
4	NDC:55728- 200-04	20 L in 1 CYLINDER; Type 0: Not a Combination Product	01/09/2012		
5	NDC:55728- 200-05	160 L in 1 DEWAR; Type 0: Not a Combination Product	01/09/2012		
6	NDC:55728- 200-06	180 L in 1 DEWAR; Type 0: Not a Combination Product	01/09/2012		
7	NDC:55728- 200-07	200 L in 1 DEWAR; Type 0: Not a Combination Product	01/09/2012		
8	NDC:55728- 200-08	623 L in 1 CYLINDER; Type 0: Not a Combination Product	01/09/2012		
9	NDC:55728- 200-09	2237 L in 1 CYLINDER; Type 0: Not a Combination Product	01/09/2012		
10	NDC:55728- 200-10	3992 L in 1 CYLINDER; Type 0: Not a Combination Product	01/09/2012		
11	NDC:55728- 200-11	6512 L in 1 CYLINDER; Type 0: Not a Combination Product	01/09/2012		

<b>12</b> NDC:55728-200-12	7787 L in 1 CYLINDER; Type 0: Not a Combination Product	01/09/2012		
200-12	Troduct			
Marketing Information				
Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date	
NDA	NDA205766	01/09/2012		

# Labeler - A & B Welding Supply Co. (007499460)

Establishment				
Name	Address	ID/FEI	<b>Business Operations</b>	
A & B Welding Supply Co.		007499460	manufacture(55728-200)	

Revised: 10/2024 A & B Welding Supply Co.