

**NITROUS OXIDE- nitrous oxide gas**  
**Crumpton Welding Supply & Equipment, Inc.**

-----  
**NITROUS OXIDE U.S.P. LABEL**

**NITROUS OXIDE USP UN1070**

NON-FLAMMABLE GAS 2 DO NOT REMOVE THIS LABEL OXIDIZER 5.1

CONTENTS: \_\_\_\_\_ LITERS \_\_\_ CU FT \_\_\_\_

**Rx only.**

**WARNING:** Administration of Nitrous Oxide may be hazardous or contraindicated. For use only by or under supervision of a licensed practitioner who is experienced in the use and administration of Nitrous Oxide and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications, and side effects and the precautions to be taken.

**WARNING:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY CAUSE DROWSINESS OR DIZZINESS. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY CAUSE FROSTBITE.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fitting free from grease and oil. Avoid breathing gas. Do not get in eyes, on skin, or on clothing. Use and store only outdoors or in a well-ventilated place. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment and compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use.

**FIRST AID: IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

**IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

**WARNING:** This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.

CAS: 10024-97-2 DO NOT REMOVE THIS PRODUCT LABEL.

*In case of emergency involving this material call INFOTRAC at 1-800-535-5053*

**CRUMPTON WELDING SUPPLY & EQUIPMENT, INC.**

1602 N 34<sup>TH</sup> STREET • TAMPA, FL 33605 • 800-229-6947

47736 (07/17)



**NITROUS OXIDE,  
USP  
UN1070**



CONTENTS: \_\_\_\_\_

CU FT   
LITERS

**R<sub>x</sub> Only.**

**WARNING:** Administration of Nitrous Oxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrous Oxide and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

**DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY CAUSE DROWSINESS OR DIZZINESS. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY CAUSE FROSTBITE.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Avoid breathing gas. Do not get in eyes, on skin, or on clothing. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet (SDS) before use.

**FIRST AID: IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

**IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

**WARNING:** This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.



CAS: 10024-97-2

DO NOT REMOVE THIS PRODUCT LABEL.

*In case of emergency involving this material call INFOTRAC at 1-800-535-5053*

**CRUMPTON WELDING SUPPLY & EQUIPMENT, INC.**

1602 N 34<sup>TH</sup> STREET • TAMPA, FL 33605 • 800-229-6947

47736  
(07/17)

# NITROUS OXIDE

nitrous oxide gas

## Product Information

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:52568-002
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

## Active Ingredient/Active Moiety

<b>Ingredient Name</b>	<b>Basis of Strength</b>	<b>Strength</b>
<b>NITROUS OXIDE</b> (UNII: K50XQU1029) (NITROUS OXIDE - UNII:K50XQU1029)	NITROUS OXIDE	99 L in 100 L

## Packaging

<b>#</b>	<b>Item Code</b>	<b>Package Description</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
1	NDC:52568-002-01	940 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
2	NDC:52568-002-02	1590 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
3	NDC:52568-002-03	4920 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
4	NDC:52568-002-04	13800 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
5	NDC:52568-002-05	91400 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
6	NDC:52568-002-06	7570 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	

## Marketing Information

<b>Marketing Category</b>	<b>Application Number or Monograph Citation</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
NDA	NDA209989	01/01/1990	

**Labeler** - Crumpton Welding Supply & Equipment, Inc. (067210450)

**Registrant** - Crumpton Welding Supply & Equipment, Inc. (067210450)

## Establishment

<b>Name</b>	<b>Address</b>	<b>ID/FEI</b>	<b>Business Operations</b>
Crumpton Welding Supply & Equipment, Inc.		067210450	manufacture(52568-002)

Revised: 10/2024

Crumpton Welding Supply & Equipment, Inc.