OXYGEN - oxygen gas DJB Gas Services, Inc

Oxygen

OXYGEN, COMPRESSED, USP UN1072

OXYGEN 2

WARNING: For emergency use only when administered properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of constructions and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect form sunlight when ambient temperature exceeds 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL

DJB Gas Services, Inc.

DJB GAS SERVICES, INC. 1177 South Swaner Road Salt Lake City, Utah 84104 801-908-7800 www.djbgas.com

CONTENTS: LTRS

CU. FT.



OXYGEN REFRIGERATED LIQUID, USP UN1073 OXYGEN 2 ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. WARNING USP For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills, Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. Lot Number: Contents: Expiration Date: DO NOT REMOVE THIS PRODUCT LABEL.





ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. WARNING DANGER FIRST AID MAY CAUSE OR INTENSIFY FIRE: USP IF ON SKIN: Thaw frosted parts with OXIDIZER. CONTAINS REFRIGERATED lukewarm water. Do not rub affected area. For emergency use only when administered GAS; MAY CAUSE CRYOGENIC BURNS Get immediate medical advice/attention. by properly trained personnel for oxygen OR INJURY, COMBUSTIBLES IN CONTACT deficiency and resuscitation. For all other WITH LIQUID OXYGEN MAY EXPLODE medical applications, Rx only. ON IGNITION OR IMPACT. Lot Number: Uninterrupted use of high concentrations Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. of oxygen over a long duration, without monitoring its effect on oxygen content of Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-Expiration Date: arterial blood, may be harmful. Do not attempt to use on patients who have ventilated place. Wear cold insulating gloves stopped breathing unless used in face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow conjunction with resuscitative equipment. preventive device in the piping. Use only with equipment of compatible materials of construction Produced by Air Liquefaction. Keep out of reach of children; and and rated for cylinder pressure. Use only with Federal law requires that this container be refilled with oxygen USP only by equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do establishments registered as a drug manufacturer in accordance with the not walk on or roll equipment over spills. Close valve after each use and when empty. Always Federal Food, Drug, and Cosmetic Act. keep container in upright position. READ AND FOLLOW THE SAFETY DATA SHEET (SDS) BEFORE USE. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL PRINTED BY RATERMANN MFG., INC.

DJB Gas Services, Inc. DJB GAS SERVICES, INC. 1177 South Swaner Road Salt Lake City, Utah 84104

801-908-7800 . www.djbgas.com

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills, Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL. CAS: 7782-44-7



OXYGEN oxygen gas Product Information Product Type PRESCRIPTION ANIMAL DRUG Item Code (Source) NDC:43621-011 Route of Administration RESPIRATORY (INHALATION) Active Ingredient/Active Moiety

	Ingredient Name	Basis of Strength	Strength
Oxyge	en (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	990 mL in 1 L

Packaging						
#	Item Code	Package Description	Marketing Start Date	Marketing End Date		
1	NDC:43621-011-11	198 L in 1 CYLINDER				
2	NDC:43621-011-12	255 L in 1 CYLINDER				
3	NDC:43621-011-13	425 L in 1 CYLINDER				
4	NDC:43621-011-14	708 L in 1 CYLINDER				
5	NDC:43621-011-15	1133 L in 1 CYLINDER				
6	NDC:43621-011-16	16 14 L in 1 CYLINDER				
7	NDC:43621-011-17	2265 L in 1 CYLINDER				
8	NDC:43621-011-18	3539 L in 1 CYLINDER				
9	NDC:43621-011-19	7108 L in 1 CYLINDER				
10	NDC:43621-011-20	9543 L in 1 CYLINDER				
11	NDC:43621-011-21	180 L in 1 DEWAR				

Marketing Information							
Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date				
NADA	NADA141354	0 1/0 1/19 9 0					

Labeler - DJB Gas Services, Inc (053129180)

Establishment							
Name	Address	ID/FEI	Business Operations				
DJB Gas Services, Inc		053129180	manufacture				

Revised: 5/2016 DJB Gas Services, Inc