

**OXYGEN- oxygen gas**  
**BUCKEYE WELDING SUPPLY COMPANY, INC.**

-----  
**Oxygen**

OXYGEN, COMPRESSED USP

UN1072

PRODUCED BY AIR LIQUEFACTION

**WARNING:** For emergency use only when administered by properly trained for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen contents of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

**DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow all Safety Data Sheet (SDS) before use. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

Buckeye Welding Supply

360 East 8th Street Greeley, CO 80631

In Case of Emergency Call

800-255-3924

NO SMOKING

NO VAPING

CONTENTS: LTRS: CU.FT.



REFRIGERATED LIQUID

OXYGEN, REFRIGERATED LIQUID USP

UN1073

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

DO NOT CHANGE OR FORCE FIT CONNECTIONS.

CONTENTS: LTRS: CU.FT.

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

**DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT.

Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use only outdoors or with adequate ventilation. Store in a well-ventilated place. Wear cold insulating gloves and either face shield or eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

**FIRST AID:** IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected



Active Ingredient/Active Moiety		
Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	992 mL in 1 L

Packaging				
#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:53729-0002-1	170 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/1987	
2	NDC:53729-0002-2	248 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/1987	
3	NDC:53729-0002-4	670 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/1987	
4	NDC:53729-0002-3	410 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/1987	
5	NDC:53729-0002-5	3894 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/1987	
6	NDC:53729-0002-6	7107 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/1987	
7	NDC:53729-0002-7	9514 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/1987	
8	NDC:53729-0002-8	180 L in 1 DEWAR; Type 0: Not a Combination Product	09/01/1987	

Marketing Information			
Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205827	09/01/1987	

**Labeler** - BUCKEYE WELDING SUPPLY COMPANY, INC. (095156451)

Establishment			
Name	Address	ID/FEI	Business Operations
BUCKEYE WELDING SUPPLY COMPANY, INC.		095156451	manufacture(53729-0002) , transfill(53729-0002)

Establishment			
Name	Address	ID/FEI	Business Operations
BUCKEYE WELDING SUPPLY COMPANY, INC.		825593908	repack(53729-0002)

Revised: 12/2025

BUCKEYE WELDING SUPPLY COMPANY, INC.