

**OXYGEN- oxygen gas**  
**BUCKEYE WELDING SUPPLY COMPANY, INC.**

-----  
**Oxygen**

OXYGEN, COMPRESSED USP

UN1072


WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

Buckeye Welding Supply

360 East 8th Street. Greeley, CO 80631

In case of Emergency Call

800-255-3924



OXYGEN REFRIGERATED LIQUID, USP

UN1073

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

WARNING

USP

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

Keep out of reach of children; and Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

DANGER

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do

so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position.

READ AND FOLLOW THE SAFETY DATA SHEET (SDS) BEFORE USE.

CAS: 7782-44-7

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

Lot Number:

Contents:

Expiration Date:

BUCKEYE WELDING SUPPLY

GREELY, CO

970-356-7546

DO NOT REMOVE THIS PRODUCT LABEL.

**OXYGEN**  
REFRIGERATED LIQUID, USP  
UN 1073

**OXYGEN 2**  
(R-X14)

**ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.**

**WARNING**  
**USP**  
For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.  
Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.  
Produced by Air Liquefaction. Keep out of reach of children; and Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.  
**READ AND FOLLOW THE SAFETY DATA SHEET (SDS) BEFORE USE.**  
CAS: 7782-44-7

**DANGER**  
MAY CAUSE OR INTENSIFY FIRE; OXIDIZER, CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.  
Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shields, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position.

**FIRST AID**  
IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.  
Lot Number:  
Contents:  
Expiration Date:

BUCKEYE WELDING SUPPLY  
GREELY, CO  
(970) 356 - 7546

**DO NOT REMOVE THIS PRODUCT LABEL**

PRINTED BY RATERMANN MFG., INC.  
www.ratermann.com

<b>OXYGEN</b>			
oxygen gas			
<b>Product Information</b>			
<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:53729-0002(NDC:11054-009)
<b>Route of Administration</b>	RESPIRATORY		

**Route of Administration** (INHALATION)

### Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	992 mL in 1 L

### Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:53729-0002-1	170 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/1987	
2	NDC:53729-0002-2	248 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/1987	
3	NDC:53729-0002-4	670 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/1987	
4	NDC:53729-0002-3	410 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/1987	
5	NDC:53729-0002-5	3894 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/1987	
6	NDC:53729-0002-6	7107 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/1987	
7	NDC:53729-0002-7	9514 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/1987	
8	NDC:53729-0002-8	180 L in 1 DEWAR; Type 0: Not a Combination Product	09/01/1987	

### Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205827	09/01/1987	

**Labeler** - BUCKEYE WELDING SUPPLY COMPANY, INC. (095156451)

### Establishment

Name	Address	ID/FEI	Business Operations
BUCKEYE WELDING SUPPLY COMPANY, INC.		095156451	manufacture(53729-0002) , transfill(53729-0002)

### Establishment

Name	Address	ID/FEI	Business Operations
BUCKEYE WELDING SUPPLY COMPANY, INC.		825593908	repack(53729-0002)

Revised: 10/2024

BUCKEYE WELDING SUPPLY COMPANY, INC.