OXYGEN- oxygen gas Community Surgical Supply of Toms River LLC

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.

Oxygen

OXYGEN

| DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. | OXYGE | N |
|---|--|--|
| Do not handle until all safety precautions have been read and keep and store away from clothing and other combustible ma | terials. Keep | - |
| valves and fittings free from grease and oil. Use and store only on a well-ventilated place. In case of fire: Stop leak if safe to do low preventive device in the piping. Use only with equipment naterials of construction and rated for cylinder pressure. Use or equipment cleaned for oxygen service. Open valve slowly. Close tech use and when empty. Protect from sunlight when ambie exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet SDS) before use. | so. Use a back t of compatible only with se valve after int temperature CAS | NO: 7782-44 |
| n a well-ventilated place. In case of fire: Stop leak if safe to do low preventive device in the piping. Use only with equipment naterials of construction and rated for cylinder pressure. Use of equipment cleaned for oxygen service. Open valve slowly. Close tach use and when empty. Protect from sunlight when ambie exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet | so. Use a back t of compatible only with se valve after ent temperature CAS Contents | Size |
| n a well-ventilated place. In case of fire: Stop leak if safe to do ow preventive device in the piping. Use only with equipment naterials of construction and rated for cylinder pressure. Use of quipment cleaned for oxygen service. Open valve slowly. Close ach use and when empty. Protect from sunlight when ambie exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet SDS) before use, NO NOT REMOVE THIS PRODUCT LABEL. | so. Use a back t of compatible only with se valve after int temperature CAS Contents 113 Liters | Size |
| n a well-ventilated place. In case of fire: Stop leak if safe to do ow preventive device in the piping. Use only with equipment naterials of construction and rated for cylinder pressure. Use of quipment cleaned for oxygen service. Open valve slowly. Clo- ach use and when empty. Protect from sunlight when ambie xceeds 52 °C (125 °F). Read and follow the Safety Data Sheet SDS) before use, NO NOT REMOVE THIS PRODUCT LABEL. VARNING: For emergency use only when administered y properly trained personnel for oxygen deficiency | so. Use a back t of compatible only with se valve after ent temperature CAS Contents 113 Liters 165 Liters | Size M4 M6 |
| a well-ventilated place. In case of fire: Stop leak if safe to do to ow preventive device in the piping. Use only with equipment naterials of construction and rated for cylinder pressure. Use or quipment cleaned for oxygen service. Open valve slowly. Clore ach use and when empty. Protect from sunlight when ambie xceeds 52 °C (125 °F). Read and follow the Safety Data Sheet (DS) before use, O NOT REMOVE THIS PRODUCT LABEL. (ARNING: For emergency use only when administered y properly trained personnel for oxygen deficiency nd resuscitation. For all other medical applications, Rx only. | so. Use a back t of compatible only with se valve after ent temperature CAS Contents 113 Liters 165 Liters 255 Liters | Size M4 M6 C |
| n a well-ventilated place. In case of fire: Stop leak if safe to do to ow preventive device in the piping. Use only with equipment naterials of construction and rated for cylinder pressure. Use or quipment cleaned for oxygen service. Open valve slowly. Close ach use and when empty. Protect from sunlight when ambie xceeds 52 °C (125 °F). Read and follow the Safety Data Sheet SDS) before use. XO NOT REMOVE THIS PRODUCT LABEL. WARNING: For emergency use only when administered and resuscitation. For all other medical applications, RX only. Ininterrupted use of high concentrations of oxygen over long duration, without monitoring its effect on oxygen | so. Use a back t of compatible only with se valve after ent temperature CAS Contents 113 Liters 165 Liters 255 Liters 425 Liters | Size Image: M4 Image: M6 Image: C Image: D |
| n a well-ventilated place. In case of fire: Stop leak if safe to do to ow preventive device in the piping. Use only with equipment naterials of construction and rated for cylinder pressure. Use or quipment cleaned for oxygen service. Open valve slowly. Close ach use and when empty. Protect from sunlight when ambie xceeds 52 °C (125 °F). Read and follow the Safety Data Sheet SDS) before use, NO NOT REMOVE THIS PRODUCT LABEL. VARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency nd resuscitation. For all other medical applications, Rx only. Ininterrupted use of high concentrations of oxygen over long duration, without monitoring its effect on oxygen ontent of arterial blood, may be harmful. Do not attempt to | so. Use a back t of compatible only with se valve after int temperature CAS Contents 113 Liters 165 Liters 255 Liters 425 Liters 680 Liters | Size M4 M6 C D E |
| n a well-ventilated place. In case of fire: Stop leak if safe to do low preventive device in the piping. Use only with equipment naterials of construction and rated for cylinder pressure. Use o quipment cleaned for oxygen service. Open valve slowly. Clo- ach use and when empty. Protect from sunlight when ambie exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet SDS) before use. | so. Use a back t of compatible only with se valve after ent temperature CAS Contents 113 Liters 165 Liters 255 Liters 425 Liters | Size Image: M4 Image: M6 Image: C Image: D |

OXYGEN COMPRESSED USP UN 1072 DANGER:

are printed in this box

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °c (125 °F). Read and follow the Safety Data Sheet (SDS) before use.

CAS NO: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency

and resuscitation. For all other medical applications, Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen

content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.



Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID:

IF ON SKIN: <u>Thaw frosted parts with lukewarm water. Do not rub affected</u> <u>area. Get immediate medical advice/attention</u>.

DO NOT REMOVE THIS PRODUCT LABEL.

Warning: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

Representative Labeling pursuant to 21 CFR 207.3 (10) Company name and contact information are printed in this area

LITERS

OXYGEN, REFRIGERATED LIQUID USP UN 1073 CONTENTS CAS NO: 7782-44-7

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use. FIRST AID:

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL.

Warning: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.



Representative Labeling pursuant to 21 CFR 207.3 (10)

| 0) | XYGEN | | | | | | |
|-----------------------------------|---|--|---|--|-----------------------|--|--|
|)X | ygen gas | | | | | | |
| - | | | | | | | |
| Product Information | | | | | | | |
| Product Type | | | HUMAN PRESCRIPTION DRUG | Item Code (Source) | NDC:57837-001 | | |
| Route of Administration | | istration | RESPIRATORY (INHALATION) | | | | |
| | | | | | | | |
| Active Ingredient/Active Moiety | | | | | | | |
| Ingredient Name | | | Basis of Strengt | th Strength | | | |
| OXYGEN (UNII: S88TT14065) (OXYGEN | | | GEN - UNII:S88TT14065) | OXYGEN | 992 mL in 1 L | | |
| P | ackaging | | | | | | |
| | ackaging | Pa | ckage Description | Marketing Start | | | |
| # | Item Code NDC:57837- | 164 L in 1 CYLI | ckage Description NDER; Type 0: Not a Combination | Marketing Start Date | Marketing End Date | | |
| # 1 | Item Code | 164 L in 1 CYLI Product | | Date | | | |
| # 1 2 | Item Code NDC:57837- 001-01 NDC:57837- | 164 L in 1 CYLI Product 255 L in 1 CYLI Product | NDER; Type 0: Not a Combination | Date 06/23/2014 | | | |
| # 1 2 3 | Item Code NDC:57837- 001-01 NDC:57837- 001-02 NDC:57837- | 164 L in 1 CYLI Product 255 L in 1 CYLI Product 425 L in 1 CYLI Product | NDER; Type 0: Not a Combination | Date 06/23/2014 06/23/2014 | | | |
| # 1 2 3 | Item Code NDC:57837- 001-01 NDC:57837- 001-02 NDC:57837- 001-03 NDC:57837- 001-03 | 164 L in 1 CYLI Product 255 L in 1 CYLI Product 425 L in 1 CYLI Product 680 L in 1 CYLI Product | NDER; Type 0: Not a Combination NDER; Type 0: Not a Combination NDER; Type 0: Not a Combination | Date 06/23/2014 06/23/2014 06/23/2014 | | | |
| # 1 2 3 4 5 | Item Code NDC:57837- 001-01 NDC:57837- 001-02 NDC:57837- 001-03 NDC:57837- 001-04 NDC:57837- | 164 L in 1 CYLI Product 255 L in 1 CYLI Product 425 L in 1 CYLI Product 680 L in 1 CYLI Product 1738 L in 1 CYLI Product | NDER; Type 0: Not a Combination NDER; Type 0: Not a Combination NDER; Type 0: Not a Combination NDER; Type 0: Not a Combination | Date 06/23/2014 06/23/2014 06/23/2014 06/23/2014 | | | |
| # 1 2 3 4 5 6 | Item Code NDC:57837- 001-01 NDC:57837- 001-02 NDC:57837- 001-03 NDC:57837- 001-04 NDC:57837- 001-05 NDC:57837- 001-05 | 164 L in 1 CYLI Product 255 L in 1 CYLI Product 425 L in 1 CYLI Product 680 L in 1 CYLI Product 1738 L in 1 CYLI Product 3455 L in 1 CYLI Product | NDER; Type 0: Not a Combination NDER; Type 0: Not a Combination NDER; Type 0: Not a Combination NDER; Type 0: Not a Combination LINDER; Type 0: Not a Combination | Date 06/23/2014 06/23/2014 06/23/2014 06/23/2014 06/23/2014 06/23/2014 | Marketing End Date | | |

| Marketing Information | | | | | | | | |
|---------------------------|---|-------------------------|-----------------------|--|--|--|--|--|
| Marketing Category | Application Number or Monograph Citation | Marketing Start Date | Marketing End Date | | | | | |
| unapproved medical gas | | 06/23/2014 | | | | | | |

Labeler - Community Surgical Supply of Toms River LLC (011771664)

Establishment

| Name | Address | ID/FEI | Business Operations |
|---|---------|-----------|----------------------------|
| Community Surgical Supply of Toms River LLC | | 011771664 | manufacture(57837-001) |

Revised: 10/2024

Community Surgical Supply of Toms River LLC