OXYGEN - oxygen gas Acetylene Oxygen Company

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.

OXYGEN COMPRESSED USP LABEL

OXYGEN COMPRESSED USP UN1072 OXYGEN-2

WARNING: FOR EMERGENCY USE ONLY WHEN ADMINISTERED BY PROPERLY TRAINED PERSONNEL FOR OXYGEN DEFICIENCY AND RESUSCITATION. FOR ALL OTHER MEDICAL APPLICATIONS Rx ONLY. UNINTERRUPTED USE OF HIGH CONCENTRATIONS OF OXYGEN OVER A LONG DURATION WITHOUT MONITORING ITS EFFECT ON OXYGEN CONTENT OF ARTERIAL BLOOD MAY BE HARMFUL. USE ONLY WITH PRESSURE REDUCING EQUIPMENT AND APPARATUS DESIGNED FOR OXYGEN. DO NOT ATTEMPT TO USE ON PATIENTS WHO HAVE STOPPED BREATHING UNLESS USED IN CONJUNCTION WITH RESUSCITATIVE EQUIPMENT. PRODUCED BY AIR LIQUEFACTION.

WARNING: HIGH PRESSURE GAS VIGOROUSLY ACCELERATES COMBUSTION. KEEP OIL AND GREASE AWAY. OPEN VALVE SLOWLY. STORE AND USE WITH ADEQUATE VENTILATION. USE ONLY WITH EQUIPMENT CLEANED FOR OXYGEN SERVICE AND RATED FOR CYLINDER PRESSURE. USE A BACK FLOW PREVENTATIVE DEVICE IN THE PIPING. CLOSE VALVE AFTER EACH USE AND WHEN EMPTY. CYLINDER TEMPERATURE SHOULD NOT EXCEED 52 C (125 F) USE IN ACCORDANCE WITH THE MATERIAL SAFETY DATA SHEET (MSDS) CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.



OXYGEN REFRIGERATED LIQUID USP LABEL

OXYGEN REFRIGERATED LIQUID USP UN1073 CONTENTS______ LITERS ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. WARNING: DO NOT CHANGE OR FORCE FIT CONNECTIONS. EXTREMELY COLD LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. NO SMOKING IN THE PRESENCE OF OXYGEN OR A FIRE MAY RESULT. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE. KEEP OIL, GREASE AND COMBUSTIBLES AWAY. USE ONLY WITH EQUIPMENT CLEANED FOR OXYGEN SERVICE. STORE AND USE WITH ADEQUATE VENTILATION. DO NOT GET LIQUID IN EYES, ON SKIN OR CLOTHING. FOR LIQUID WITHDRAWAL, WEAR FACE SHIELD AND GLOVES. DO

NOT DROP. USE SUITABLE HAND TRUCK FOR CONTAINER MOVEMENT. AVOID SPILLS. DO NOT WALK OR ROLL EQUIPMENT OVER SPILLS CONTAINER TEMPERATURE SHOULD NOT EXCEED 52C (125 F) CLOSE VALVE AFTER EACH USE AND WHEN EMPTY. USE A BACK FLOW PREVENTATIVE DEVICE IN THE PIPING. USE IN ACCORDANCE WITH THE MATERIAL SAFETY DATA SHEET (MSDS)

FIRST AID: IN CASE OF FROSTBITE OBTAIN MEDICAL TREATMENT IMMEDIATELY.

WARNING: FOR EMERGENCY USE ONLY WHEN ADMINISTERED BY PROPERLY TRAINED PERSONNEL FOR OXYGEN DEFICIENCY AND RESUSCITATION. FOR ALL OTHER MEDICAL APPLICATIONS Rx ONLY. UNINTERRUPTED USE OF HIGH CONCENTRATIONS OF OXYGEN OVER A LONG DURATION WITHOUT MONITORING ITS EFFECT ON OXYGEN CONTENT OF ARTERIAL BLOOD MAY BE HARMFUL. USE ONLY WITH PRESSURE REDUCING EQUIPMENT AND APPARATUS DESIGNED FOR OXYGEN. DO NOT ATTEMPT TO USE ON PATIENTS WHO HAVE STOPPED BREATHING, UNLESS USED IN CONJUNCTION WITH RESUSCITATIVE EQUIPMENT. PRODUCED BY AIR LIQUEFACTION. DO NOT REMOVE THIS PRODUCT LABEL.

OXYGEN, REFRIGERATED LIQUID

USP



UN1073

1 ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. **1**

CONTENTS:	
L <mark>OT #:</mark>	

WARNING:

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING:

EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER

PRESSURE.

VIGOROUSLY ACCELERATES COMBUSTION.

COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY

EXPLODE ON IGNITION OR IMPACT.

CAN CALICE CEVEDE EDOCTDITE

UAN UAUSE SEVERE PRUSIBILE.

Keep oil, grease and combustibles away.
Use only with equipment cleaned for oxygen service.
Store and use with adequate ventilation.
Do not get liquid in eyes, on skin or clothing.
For liquid withdrawal, wear face shield and gloves.
Do not drop. Use suitable hand truck for container movement.
Avoid spills. Do not walk on or roll equipment over spills.
Cylinder temperature should not exceed 52°C (125°F).
Close valve after each use and when empty.
Use a back flow preventive device in the piping.
Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment

immediately.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

ACETYLENE OXYGEN CO.

HARLINGEN, TEXAS 78550 CHEMTREC 1-800-424-9300

OXYGEN USP CERTII	FICATE OF ANALYSIS		
LOT NUMBER GALS., LITERS, CU. FT	SERIAL NUMBER	AMOUNT	INS, LBS.,
USP TESTS			
TEST ID ODOR	ASSAY		
LIMITS OK NONE	LESS THAN 99.2%		
RESULT			
FOR CUSTOMER TO U	SE TO DOCUMENT TESTS P	PERFORMED ON THIS V	ESSEL
	IS FOR ASSAY IS THE PARA: MODEL		

NO SUPPLIERS SIGNATURE DATE CUSTOMERS

SIGNATURE	_DATE			
LIQUID MEDICAL GASES L BY THIS VESSI				
RESULTS) OXYGEN PRODU				
AOC				
ACETYLENE	Modia	ool Coo		
OXYGEN COMPANY	weak	cal Gas	es	
LIQUID	OXYGEN	V DEI	IVERY T	AG
				14
FILLED AND DIS	TRIBUTED BY:			
		(
THIS VESSEL CO	ONTAINS OXYG	EN, U.S.P.	(See reverse side FACTION PROCES	for test results)
OXTGEN THOSE	SCED BY THE A	IR LIQUE	-ACTION PROCES	S
LOT NUMBER	· · · · · · · · · · · · · · · · · · ·	SERIAL	NUMBER	and the second s
AMOUNT		·	S. GALS., LITEF	
USP TESTS			R CUSTOMER USE TO ST PERFORMED ON T	
	DDOR ASSAY			
RESULT	40NE 230.270			
CUSTOMER WITNESSED TES	STS: YES			
	□ NO			
		<u> </u>		
SUPPLIER'S SIGNATURE		-1	DATE	
CUSTOMER'S SIGNATURE			The state of the s	
				9
OXYGEN				
oxygen gas				
Product Information				
Product Type	HUMAN PRESCRIPTION	DRUG	Item Code (Source)	NDC:10006-001
Route of Administration	RESPIRATORY (INHALA	ATION)		

Active Ingredient/Active Moiety		
Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

Pá	ackaging			
#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:10006-001-01	103 L in 1 CYLINDER		
2	NDC:10006-001-02	150 L in 1 CYLINDER		
3	NDC:10006-001-03	255 L in 1 CYLINDER		
4	NDC:10006-001-04	426 L in 1 CYLINDER		
5	NDC:10006-001-05	671 L in 1 CYLINDER		
6	NDC:10006-001-06	610 L in 1 CYLINDER		
7	NDC:10006-001-07	1140 L in 1 CYLINDER		
8	NDC:10006-001-08	1500 L in 1 CYLINDER		
9	NDC:10006-001-09	3462 L in 1 CYLINDER		
10	NDC:10006-001-10	6900 L in 1 CYLINDER		
11	NDC:10006-001-11	9310 L in 1 CYLINDER		
12	NDC:10006-001-12	21 L in 1 DEWAR		
13	NDC:10006-001-13	31 L in 1 DEWAR		
14	NDC:10006-001-14	41 L in 1 DEWAR		
15	NDC:10006-001-15	46 L in 1 DEWAR		
16	NDC:10006-001-16	160 L in 1 DEWAR		
17	NDC:10006-001-17	180 L in 1 DEWAR		
18	NDC:10006-001-18	176 L in 1 DEWAR		
19	NDC:10006-001-19	225 L in 1 DEWAR		

Marketing Information					
Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date		
unapproved medical gas		0 1/0 1/19 36			

Labeler - Acetylene Oxygen Company (008110181)

Registrant - Acetylene Oxygen Company (008110181)

Establishment			
Name	Address	ID/FEI	Business Operations
Acetylene Oxygen Company		127506447	manufacture

Establishment			
Name	Address	ID/FEI	Business Operations
Acetylene Oxygen Company		025250655	manufacture

Establishment				
Name	Address	ID/FEI	Business Operations	
Acetylene Oxygen Company		153366138	manufacture	

Establishment				
Name	Address	ID/FEI	Business Operations	
Acetylene Oxygen Company		809888688	manufacture	

Establishment			
Name	Address	ID/FEI	Business Operations
Acetylene Oxygen Company		047022553	manufacture

Establishment			
Name	Address	ID/FEI	Business Operations
Acetylene Oxygen Company		809889033	manufacture

Establishment			
Name	Address	ID/FEI	Business Operations
Acetylene Oxygen Company		964420496	manufacture

Revised: 4/2011 Acetylene Oxygen Company