OXYGEN- oxygen gas CONROE WELDING SUPPLY, INC.

Oxygen

REFRIGERATED LIQUID

OXYGEN, REFRIGERATED LIQUID USP

UN1073

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

DO NOT CHANGE OR FORCE FIT CONNECTIONS.

CONTENTS: LTRS: CU.FT.

WARNING: USP For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.


Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL. CONROE WELDING 415 SOUTH FRAZIER CONROE, TX 77301 936-539-3124



OXYGEN, COMPRESSED USP

UN1070

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

CONROE WELDING

415 SOUTH FRAZIER CONROE, TX 77301

936-539-3124

OXYGEN, COMPRESSED USP foral AIS SOUTH FAULTER + CONTOC - X/T301 AIS SOUTH FAULTER + CONTOC - X/T301 936-539-3124 UN1072 OXYGEN 2

| | KYGEN | | | | | |
|---|--|--|--|---|-----------------------|--|
| oxygen gas | | | | | | |
| - | | | | | | |
| Pı | roduct Infor | mation | | | | |
| Product Type Route of Administration | | | HUMAN PRESCRIPTION DRUG | Item Code (Source) | NDC:54244-001 | |
| | | istration | RESPIRATORY (INHALATION) | | | |
| | | | | | | |
| Ac | tive Ingred | ent/Active | Moiety | | | |
| Ingredient Name | | | ent Name | Basis of Strengt | h Strength | |
| OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065) OXYGEN | | | 995 mL in 1 L | | | |
| Packaging | | | | | | |
| | | | | Marketing Start | Marketing End | |
| # | Item Code | Pa | ckage Description | Marketing Start Date | Marketing End Date | |
| # 1 | Item Code NDC:54244- 001-01 | | Ackage Description | - | | |
| | NDC:54244- | 240 L in 1 DEV Product | | Date | | |
| 1 | NDC:54244- 001-01 NDC:54244- | 240 L in 1 DEV Product 180 L in 1 DEV Product | VAR; Type 0: Not a Combination | Date 09/05/1974 | • | |
| 1 2 | NDC:54244- 001-01 NDC:54244- 001-02 NDC:54244- | 240 L in 1 DEV Product 180 L in 1 DEV Product 160 L in 1 DEV Product | VAR; Type 0: Not a Combination | Date 09/05/1974 09/05/1974 09/05/1974 | | |
| 1 2 3 | NDC:54244- 001-01 NDC:54244- 001-02 NDC:54244- 001-03 NDC:54244- | 240 L in 1 DEV Product 180 L in 1 DEV Product 160 L in 1 DEV Product 6900 L in 1 CY Product | VAR; Type 0: Not a Combination VAR; Type 0: Not a Combination VAR; Type 0: Not a Combination | Date 09/05/1974 09/05/1974 09/05/1974 09/05/1974 09/05/1974 | | |

| M | arketing Marketing Category | Information Application Number or Monograph Citation | Marketing Start Date | Marketing End Date | | | | |
|----|-----------------------------------|--|-------------------------|-----------------------|--|--|--|--|
| Μ | arketing | Information | | | | | | |
| | Marketing Information | | | | | | | |
| | | | | | | | | |
| 10 | NDC:54244- 001-10 | 165 L in 1 CYLINDER; Type 0: Not a Combination Product | 09/05/1974 | | | | | |
| 9 | NDC:54244- 001-09 | 248 L in 1 CYLINDER; Type 0: Not a Combination Product | 09/05/1974 | | | | | |
| 8 | NDC:54244- 001-08 | 415 L in 1 CYLINDER; Type 0: Not a Combination Product | 09/05/1974 | | | | | |
| | 001-07 | 682 L in 1 CYLINDER; Type 0: Not a Combination Product | 09/05/1974 | | | | | |

Labeler - CONROE WELDING SUPPLY, INC. (074194994)

| Establishment |
|---------------|
|---------------|

| Name | Address | ID/FEI | Business Operations |
|-----------------------------|---------|-----------|----------------------------|
| CONROE WELDING SUPPLY, INC. | | 074194994 | manufacture(54244-001) |

Revised: 10/2024

CONROE WELDING SUPPLY, INC.