OXYGEN- oxygen gas Holston Gases, Inc.

Oxygen

OXYGEN, COMPRESSED USP UN1072 OXYGEN 2

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. PRODUCED BY AIR LIQUIFACTION DANGER: MAY CAUSE OR INTENCIFY FIRE; OXYDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL CONTENTS: LTRS: CU.FT. HOLSTON GASES 545 W. BAXTER AVENUE KNOXVILLE, TN 37921 865-573-1917



REFRIGERATED LIQUID OXYGEN, REFRIGERATED LIQUID USP UN1073 OXYGEN 2 ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. CONTENTS: LTRS: CU FT: WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be filled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills, Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

HOLSTON GASES 368 TERRY BLVD. LOUISVILLE, KY 40229 502-955-5928



OXYGEN, REFRIGERATED LIQUID, USP UN1073 OXYGEN 2 HOLSTON GASES 545 W. BAXTER AVENUE KNOXVILLE, TN 37921 865-573-1917 ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. Keep out of reach of children. Federal law requires that this container be filled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills, Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL CAS: 7782-44-7



OXYGEN

oxygen gas

Produc	t Infor	mation
Proauc	LIIIOF	шанон

Product Type PRESCRIPTION ANIMAL DRUG Item Code (Source) NDC:55050-1000

Route of Administration RESPIRATORY (INHALATION)

Active Ingredient/Active Moiety

Ingredient Name Basis of Strength Strength

OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)

OXYGEN 99 L in 100 L

P	Packaging				
#	Item Code	Package Description	Marketing Start Date	Marketing End Date	
1	NDC:55050-1000-1	426 L in 1 CYLINDER			
2	NDC:55050-1000-2	725 L in 1 CYLINDER			
3	NDC:55050-1000-3	3462 L in 1 CYLINDER			
4	NDC:55050-1000-4	7108 L in 1 CYLINDER			
5	NDC:55050-1000-5	9543 L in 1 CYLINDER			
6	NDC:55050-1000-6	127440 L in 1 DEWAR			

Marketing InformationMarketing CategoryApplication Number or Monograph CitationMarketing Start DateMarketing End DateNADANADA14138701/01/1958

Registrant - Holston Gases, Inc. (034697276)

Establishment			
Name	Address	ID/FEI	Business Operations
Holston Gases, Inc.		034697276	manufacture

Establishment			
Name	Address	ID/FEI	Business Operations
Holston Gases, Inc.		606206761	manufacture

Establishment			
Name	Address	ID/FEI	Business Operations
Holston Gases, Inc.		829338115	manufacture

Establishment			
Name	Address	ID/FEI	Business Operations
Holston Gases, Inc.		024270741	manufacture

Establishment			
Name	Address	ID/FEI	Business Operations
Holston Gases, Inc.		078483637	manufacture

Revised: 2/2016 Holston Gases, Inc.