

**OXYGEN - oxygen liquid**  
**Dressel Welding Supply, Inc.**

*Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.*

**Liquid Oxygen Label**

**OXYGEN,  
 REFRIGERATED  
 LIQUID  
 USP**



**UN1073**

Produced by Air Liquefaction.

**DRESSEL WELDING SUPPLY, INC.**  
 YORK, PA  
 www.dresselweldingsupply.com

↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑

**SECURE ALL CYLINDERS WHILE IN STORAGE AND IN USE.**

**WARNING:**

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only.**  
**Caution: Federal law prohibits dispensing without prescription.**

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

**CAS: (7782-44-7)**

**WARNING:**

**EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.**  
 Keep oil, grease and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Cylinder temperature should not exceed 52°C (125°F). Close valve after each use and when empty. Use in accordance with the Material Safety Data Sheet (MSDS).

**IN CASE OF FROSTBITE, obtain medical treatment immediately.**

**DO NOT REMOVE THIS PRODUCT LABEL**

Oxygen, Refrigerated Liquid USP UN1073 Produced by Air Liquefaction. Dressel Welding Supply, Inc. York, PA www.dresselweldingsupply.com Always keep container in upright position. Secure all cylinders while in storage and in use. Warning: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Caution: Federal law prohibits dispensing without a prescription. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. CAS (7782-44-7) Warning: Extremely cold oxidizing liquid and gas under pressure. Vigorously accelerates combustion. Combustibles in contact with liquid oxygen may explode on ignition or impact. Can cause severe frostbite. Keep oil, grease and combustibles away. Use only with equipment cleaned for oxygen service. Store and use adequate ventilation. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Close valve after each use and when empty. Use in accordance with the Material Safety Data Sheet (MSDS). In case of frostbite, obtain medical treatment immediately. Do not remove this product label.

**OXYGEN**

oxygen liquid

**Product Information**

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:52072-002
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

**Active Ingredient/Active Moiety**

<b>Ingredient Name</b>	<b>Basis of Strength</b>	<b>Strength</b>
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	992 L in 1000 L

**Packaging**

<b>#</b>	<b>Item Code</b>	<b>Package Description</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
1	NDC:52072-002-01	136567 L in 1 CYLINDER		
2	NDC:52072-002-02	293263 L in 1 TANK		
3	NDC:52072-002-03	387759 L in 1 TANK		
4	NDC:52072-002-04	814620 L in 1 TANK		

**Marketing Information**

<b>Marketing Category</b>	<b>Application Number or Monograph Citation</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
unapproved medical gas		12/23/2004	

**Labeler** - Dressel Welding Supply, Inc. (015146988)**Establishment**

<b>Name</b>	<b>Address</b>	<b>ID/FEI</b>	<b>Business Operations</b>
Dressel Welding Supply, Inc.		004573542	manufacture

**Establishment**

<b>Name</b>	<b>Address</b>	<b>ID/FEI</b>	<b>Business Operations</b>
Dressel Welding Supply, Inc.		784644416	manufacture

**Establishment**

<b>Name</b>	<b>Address</b>	<b>ID/FEI</b>	<b>Business Operations</b>
Dressel Welding Supply, Inc.		947251745	manufacture

Revised: 12/2009

Dressel Welding Supply, Inc.