

OXYGEN- oxygen gas
GIBBS WELDING SUPPLY, INC.

oxygen

OXYGEN, Refrigerated Liquid USP
UN 1073

GIBBS WELDING SUPPLY, INC.

875 VISCO DRIVE, NASHVILLE, TN 37210 (615) 254-1457

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

WARNING:

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use only outdoors or with adequate ventilation. Store in a well-ventilated place. Wear cold insulating gloves and either face shield or eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. **DO NOT** change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL.

CAS: 7782-44-7

NO SMOKING

NO VAPING

**OXYGEN,
Refrigerated
Liquid
USP**

UN 1073

GIBBS WELDING SUPPLY, INC.
875 VISCO DRIVE, NASHVILLE, TN 37210

(615) 254-1457



ALWAYS KEEP CONTAINER IN UPRIGHT POSITION
WARNING:

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use only outdoors or with adequate ventilation. Store in a well-ventilated place. Wear cold insulating gloves and either face shield or eye protection. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.



FIRST AID
IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.
DO NOT REMOVE THIS PRODUCT LABEL.
CAS: 7782-44-7



**NO SMOKING
NO VAPING**

OXYGEN, COMPRESSED USP
UN1072

PRODUCED BY AIR LIQUEFACTION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

GIBBS WELDING SUPPLY, INC.
875 VISCO DRIVE, NASHVILLE, TN 37210
(615) 254-1457

CONTENTS:

LTRS:

CU.FT

NO SMOKING

NO VAPING

OXYGEN,
COMPRESSED
USP
UN1072
PRODUCED BY AIR LIQUEFACTION



WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use.

GIBBS WELDING SUPPLY, INC.
875 VISCO DRIVE, NASHVILLE, TN 37210

CONTENTS:
Ltrs.
Cu. Ft.



NO SMOKING
NO VAPING

OXYGEN, COMPRESSED USP
UN1072

C.A.S. NO. 7782-44-7

GIBBS WELDING SUPPLY, INC.

875 VISCO DRIVE, NASHVILLE, TN 37210

(615) 254-1457

NO SMOKING

NO VAPING

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.


Produced by Air Liquefaction.

Size Contents Size Contents

M6 170 Liters E 682 Liters

C 248 Liters H 6910 Liters

D 415 Liters Other Liters



OXYGEN

oxygen gas

Product Information

Product Type	PRESCRIPTION ANIMAL DRUG	Item Code (Source)	NDC:58632-011
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:58632-011-01	7952 L in 1 CYLINDER		
2	NDC:58632-011-02	170 L in 1 CYLINDER		
3	NDC:58632-011-03	618 L in 1 CYLINDER		
4	NDC:58632-011-04	415 L in 1 CYLINDER		
5	NDC:58632-011-05	2264 L in 1 CYLINDER		
6	NDC:58632-011-06	3537 L in 1 CYLINDER		

7 NDC:58632-011-07 5468 L in 1 DEWAR

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NADA	NADA141354	07/01/2005	

Labeler - GIBBS WELDING SUPPLY, INC. (621442615)

Establishment

Name	Address	ID/FEI	Business Operations
GIBBS WELDING SUPPLY, INC.		621442615	manufacture

Revised: 10/2025

GIBBS WELDING SUPPLY, INC.