

OXYGEN- oxygen gas
Depke Welding Supplies, Inc.

Oxygen

OXYGEN, COMPRESSED, USP
UN1072

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

Depke GASES AND WELDING SUPPLIES

628 E WILLIAMS ST
DANVILLE, IL 61832

1-800-38-DEPKE

NO SMOKING

NO VAPING

Contents:

T-323 CF E Pur-23 CF

K-238 CF DD-22 CF

E, M-118 CF D Pur-14 CF

Q-81 CF M9-8.5 CF

M60-57 CF M6-5.7 CF



REFRIGERATED LIQUID
 OXYGEN, REFRIGERATED LIQUID USP
 UN1073

CONTENTS: LTRS: CU FT:

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves and either face shield or eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only with equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Always keep container in upright position. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL

NO SMOKING

NO VAPING

Depke GASES AND WELDING SUPPLIES

628 E WILLIAMS ST

DANVILLE, IL 61832
1-800-38-DEPKE

REFRIGERATED LIQUID

**OXYGEN,
REFRIGERATED
LIQUID
USP**

UN1073



CONTENTS: _____ LTRS:
_____ CU FT:

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **R. required.**

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves and either face shield or eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Always keep container in upright position. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL



NO SMOKING
NO VAPING



628 E WILLIAMS ST
DANVILLE, IL 61832
1-800-38-DEPKE

47136
[01/05]

OXYGEN			
oxygen gas			
Product Information			
Product Type	PRESCRIPTION ANIMAL DRUG	Item Code (Source)	NDC:10690-011
Route of Administration	RESPIRATORY (INHALATION)		
Active Ingredient/Active Moiety			
Ingredient Name	Basis of Strength	Strength	
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	995 mL in 1 L	
Packaging			
#	Item Code	Package Description	Marketing Start Date
1	NDC:10690-011-01	163 L in 1 CYLINDER	
2	NDC:10690-011-02	236 L in 1 CYLINDER	
3	NDC:10690-011-03	396.43 L in 1 CYLINDER	
4	NDC:10690-011-04	651.28 L in 1 CYLINDER	

5	NDC:10690-011-05	1699.01 L in 1 CYLINDER		
6	NDC:10690-011-06	3341.3 L in 1 CYLINDER		
7	NDC:10690-011-07	6739.34 L in 1 CYLINDER		
8	NDC:10690-011-08	9344.5 L in 1 CYLINDER		
9	NDC:10690-011-09	127425.8 L in 1 DEWAR		
10	NDC:10690-011-10	162963.452 L in 1 DEWAR		
11	NDC:10690-011-11	235926.905 L in 1 DEWAR		
12	NDC:10690-011-12	387855.849 L in 1 DEWAR		
13	NDC:10690-011-13	621413.201 L in 1 DEWAR		
14	NDC:10690-011-14	945188.026 L in 1 DEWAR		
15	NDC:10690-011-15	160 L in 1 CYLINDER		
16	NDC:10690-011-16	200 L in 1 CYLINDER		

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NADA	NADA141396	01/01/1978	

Labeler - Depke Welding Supplies, Inc. (025382276)

Establishment

Name	Address	ID/FEI	Business Operations
PRATT SUPPLIES INC. dba Depke Welding Supplies, Inc		041939869	manufacture

Revised: 10/2025

Depke Welding Supplies, Inc.